



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## 8173A6507 Control Unit Din Rail DC *Eaton Corp*

|                  |   |
|------------------|---|
| Catalog Number   | 8173A6507   |
| Manufacturer     | Eaton Corp  |
| Description      | Photoelectric Sensor, Polystyrene Material, Screw Terminal Connection, -32 to +131 °F, 2.66 In Overall Length, 1.3 In Overall Width, 3.06 In Overall Height, Din Rail Mount, 4 LB |
| Weight per unit  | 0.6000 (lbs/each)   |
| Product Category | Sensor Accessories  |

### Features

|            |                                   |
|------------|-----------------------------------|
| connection | Screw Terminal                    |
| dimensions | 2.6600 IN X 1.3000 IN X 1.7000 IN |

### Descriptions

|                        |  |
|------------------------|--|
| Description            | CONTROL UNIT DIN RAIL DC   |
| extra long description | ETN 8173A-6507 CONTROL UNIT DIN RAI  |
| Features               | The 70 series offers a wide choice of sensor heads, control units, output devices, logic modules, and accessories to solve virtually any problem. Sensor heads are connected by cables to the control unit and can be mounted up to 1000 ft away. They are available in thru-beam, reflex, diffuse reflective, fiber optic, Curtain-of-Light and slot-style optical modes. |

### Manufacturer Information

|       |                     |
|-------|---------------------|
| Brand | EATON CUTLER-HAMMER |
| GTIN  | 00782113028217      |
| UPC   | 782113028217        |

### Taxonomies, Classifications, and Categories

|                      |                                 |
|----------------------|---------------------------------|
| Category Description | PROXIMITY SWITCHES AND CORDSETS |
| Type                 | Photoelectric sensor accessory  |

### Packaging

|                 |     |
|-----------------|-----|
| Carton          | 1   |
| Weight Per each | 0.6 |

### Uses, Certifications, and Standards

|                                |   |
|--------------------------------|---|
| Application                    | Elec Assemblies, Panels & OEM - Electrical Assemblies, Panels and OEMs      |
| Operating Temperature standard | 32° to 131°F (0° to 55°C)<br>UL Listed, CSA Certified, Contact Manufacturer |