

Packaging

Carton

Weight Per each

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



	89610 Barrier Strip, 12-Circuit Ideal
Catalog Number	89610
Manufacturer	ldeal
Description	Barrier Strip, 12 Circuits, 10 Poles, 30 A, 300/400 V, Plastic, +221 °F, 4.626 In Overall Length, 0.795 In Overall Width, 0.570 In Overall Height, 0.13 LB
Weight per unit	•
Draduat Catagory	Power BLKS & Distribution BLKS
Features	
amparaga rating	20/30
Material	Plastic
Voltage Rating	
Wire Size	22-10, 22-18
Descriptions	
Description	BARRIER STRIP, 12-CIRCUIT
extra long description	-
Features	IDEAL Barrier Strips are designed and manufactured to be rugged, reliable, and easy to use. A thermoplastic base and corrosion-resistant screws and hardware provide extended service life.
Special Features	Features: UL Recognized For 30A, 300V; CSA Certified For 20A, 400V; Torque Rating Of 4.4 In-Lbs; Recessed Screws And Tubular Contacts; UL Listed And CSA Certified; Connect Stripped Un-Terminated Solid Or Stranded Wire; Modular 12 Circuits Can Be Cut Into Smaller Sections; Plastic Housing Is UL Flame Rated To 94V-2; Rated Temperature To 105 Degrees C; Recessed Screws And Tubular Contacts Provide Added Safety And Help Prevent Short Circuits; Tubular Contacts Connect Stripped, Un-Terminated Solid Or Stranded W
Manufacturer Informa	tion
Brand	Ideal
GTIN	00783250896103
UPC	783250896103
Taxonomies, Classificate Category Description	tions, and Categories Datacom Wiring Devices and Accessories

1

0.133

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certificat	tions, and	l Stand	ards
------------------	------------	---------	------

standard	C/US UL Listed, RoHS