16 AWG, 14 AWG, 12 AWG 2 Conductor Type CL2 Zip Parallel Speaker Cable



CONSTRUCTION:

1. Conductors: 2. Insulation: Two conductor, Class B stranded bare copper , The copper is 99.90% oxygen free. PVC, Color: Clear

APPLICATIONS AND FEATURES:

General Purpose Power Limited Circuit Cable. Commercial audio zip speaker Cable.

SPECIFICATIONS:

- UL 13 CL2, NEC article 725
- CSA FT1 Flame Test
- CSA CMH

• RoHS-2 (European Directive 2011/65/EU)

SAMPLE PRINT LEGEND:

SOUTHWIRE® 946XX XX AWG 2/C STR SPEAKER CABLE C(ETL)US TYPE CL2 -- TYPE CMH FT1

PACKAGING

Standard Length: 500FT Reel, other lengths are available upon request.

TABLE 1 - WEIGHTS & MEASUREMENTS

Stock Code	Cond. Size (AWG)	No. of Cond.	No. of Strands	Insulation Thickness (Inch)	Insulation Thickness (mm)	Single wire Nom OD (Inch)	Single wire Nom OD (mm)	Nominal Weight (Lbs/Mft)	Nominal Weight (kg/km)
946160518	16	2	65/34	0.034	0.864	0.126	3.200	34.000	50.592
946140518	14	2	105/34	0.042	1.067	0.157	3.988	52.000	77.376
946120518	12	2	168/34	0.046	1.168	0.193	4.902	81.000	120.528

All dimensions are nominal and subject to nominal manufacturing tolerances

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Southwire's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Southwire or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Southwire's standard terms and conditions contained therein, including without limitation Southwire's standard warranty. Southwire disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Southwire. Any information contained herein shall not be disclosed to any party without written consent of Southwire.



Southwire Company, LLC | One Southwire Drive, Carrollton, GA 30119 | www.southwire.com

Copyright © 2016 Southwire Company, LLC. All Rights Reserved

SPEC 70416

Southwire All rights reserved, Specifications are subject to change without notice.



DATE: 9/19/2018 Rev 1