


Insulating Bushings - Knockout

Images



Application

Converts metallic box rough edged knockout holes to smooth insulated holes for protection of electrical and telecommunications cable. Rated 105 Degrees C.

Product Information

Material: Plastic
Finish: Natural

Certifications & Codes:

CSA File Number: LR24719
NEMA Standard: FB-1
UL Standard: UL-514B
UNSPSC: 39121312

[Download Photo Image](#)

[Download Dimensional Image](#)

Dimension A in Inches: 13/16
Dimension B in Inches: 1-3/16
Dimension C in Inches: 1-1/8

Catalog ID: 9792

UPC Number: 781747007926

Description: Bushing, Insulating, Plastic Rated 105 Degrees C, 1.125 Inch Hole Dia.

Application: Converts metallic box rough edged knockout holes to smooth insulated holes for protection of electrical and telecommunications cable. Rated 105 Degrees C.

Trade Size: 3/4"


Country of Manufacture: USA

Std Pkg Qty: 1000

Unit Qty: 100

Insulating Bushings - Knockout

Images



Application

Converts metallic box rough edged knockout holes to smooth insulated holes for protection of electrical and telecommunications cable. Rated 105 Degrees C.

Product Information

Material: Plastic
Finish: Natural

Certifications & Codes:

CSA File Number: LR24719
NEMA Standard: FB-1
UL Standard: UL-514B
UNSPSC: 39121312

[Download Photo Image](#)

[Download Dimensional Image](#)

Dimension A in Inches: 13/16
Dimension B in Inches: 1-3/16
Dimension C in Inches: 1-1/8

Catalog ID: 9792

UPC Number: 781747007926

Description: Bushing, Insulating, Plastic Rated 105 Degrees C, 1.125 Inch Hole Dia.

Application: Converts metallic box rough edged knockout holes to smooth insulated holes for protection of electrical and telecommunications cable. Rated 105 Degrees C.

Trade Size: 3/4"

Country of Manufacture: USA

Std Pkg Qty: 1000

Unit Qty: 100