

# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



#### **A515MW 15 Min Twist Timer White**

Nsi Industries

Catalog Number	A515MW
Manufacturer	Nsi Industries
Description	Interval Timer 15 Min White
Weight per unit	0.4000 (lbs/each)
Product Category	Electromechanical Time Switche

#### **Features**

action	SPDT
Base	Wall Plate
Contact Rating	125-250-277 VAC
Phase	Single Phase
Poles	1
Timing Range	15 Minute

## **Dimensions and Weight**

Size H=5.00 - W=3.00

#### **Descriptions**

,sor iptions	
Description	15 MIN TWIST TIMER WHITE
extra long description	TORK A515MW Interval Timer 30 Min I
Features	Tork 15 min Twist Timer No Hold- White APPLICATIONS: Whole House Fans, Indoor/Outdoor Lighting, Bathroom Fans and Lights, Self Storage. FEATURES: COLOR: White VARIABLE TIMING: Twist knob for time ON setting up to 15 minutes. HOLD FEATURE: No Hold on this model. EASY SET: No adjustments. Just wire and go, EASY WIRING: No neutral required. Great for retrofit, Use as single or in multi-gang box with no de-rating. SWITCH TYPE: SPST "2 in 1" contacts wire has SPST also WALL PLATE: Fits standard or decorator st
Long Description	Interval Timer 15 Min White
Product Type	Interval Timer 30 Min Ivory
Special Features	White 15 Minute No Hold In Wall Time Switch
anufacturer Information Brand	NSi

#### Ma

Brand	NSi	
GTIN	00786261151131	
Manufacturers Part Number	A515MW	
UPC	786261151131	

### **Taxonomies, Classifications, and Categories**

Category Description	TIME CLOCKS
Type	Spring Wound In Wall Time Switch



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

		^	•	^	$\sim$	-	
_	a	-	ĸ	-	,		
	61	۱.	•				

Carton	1	
Weight Per each	0.4	

#### **Uses, Certifications, and Standards**

Application	NSI
Enclosure	Single Gang Wall Plate
environmental conditions	32-122 F
Frequency Rating	50-60 Hz
Mounting	Single Gang Wall Plate
Operating Temperature	32-122 F
standard	cULus