



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1207 Energy Drive
75662-0000, TX Kilgore
Phone: 903-984-8485
Fax: 903-984-8193



AH420P7W Plug Pin & Sleeve 20A 480V 3PH 3P4W WT RD

Eaton Wiring Devices

Catalog Number	AH420P7W
Manufacturer	Eaton Wiring Devices
Description	Eaton Arrow Hart Pin and Sleeve Plug, IP69K Rated, #12 - #10 Awg, 20A, 3Ø 480V, Back Wire, Red, Nickel Plated Brass, IP67, Nylon, Three-Pole, Four-Wire, Grounding, 0.333-0.775IN (0.85-1.97CM), Male, 5 HP, Nylon, Three-Phase
Weight per unit	160.0 (lbs/each)
Product Category	Plugs, Connectors, Inlets, Out

Features

dimensions	8.5000 IN X 4.3750 IN X 4.3750 IN
Material	Nylon
media	Yes

Descriptions

Description	PLUG PIN & SLEEVE 20A 480V 3PH 3P4W WT RD
extra long description	EWD AH420P7W Plug Pin&Sleeve 20A 48
Features	Eaton's Arrow Hart full line of pin and sleeve devices offer sturdy nylon construction, rugged design with corrosion resistant components for lasting electrical performance, and watertight sealing that provides IP69K protection so you can feel confident in even the most severe washdown environments.
Long Description	Eaton Arrow Hart pin and sleeve plug, IP69K Rated, #12 - #10 AWG, 20A, 3Ø 480V, Back wire, Red, Nickel plated brass, IP67, Nylon, Three-pole, Four-wire, grounding, 0.333-0.775in (0.85-1.97cm), Male, 5 HP, Nylon, Three-phase
Product Type	Plug Pin&Sleeve 20A 480V 3PH 3P4W WT RD
Special Features	Watertight P&S plugs

Manufacturer Information

Brand	Eaton
GTIN	00032664733499
Manufacturers Part Number	AH420P7W
UPC	032664733499

Taxonomies, Classifications, and Categories

Category Description	Pin & Sleeve Devices
Type	Pin and Sleeve plug

Packaging

Carton	1
Package	160
Weight Per each	160



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1207 Energy Drive
75662-0000, TX Kilgore
Phone: 903-984-8485
Fax: 903-984-8193

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
standard	cRUus