

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



ALF114200 1 1/4" Alu Flexible Conduit 200'

Southwire Company

Catalog Number	ALF114200
Manufacturer	Southwire Company
Description	UI Reduced Wall Aluminum Type RW Fac, 5600 Series, Lightweight Reduced Wall Aluminum Flexible Conduit. Premium Aluminum Alloy. Interlocking Design. 1-1/4 Inch Diameter, 200 Foot Reel
Weight per unit	44.0 (lbs/ft)
Product Category	Flexible Metallic Conduit
Features	
Inside Diameter	1.250/1.300
Material	Aluminum
outside diameter	1.550/1.630
Material, Color, and Finish	
Color	Gray
Finish	Aluminum Alloy
Dimensions and Weight Length	200
Longin	200



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

. 1	~~	~ "	•	-
		1 - E	11	ns
_			JL	

Weight

Weight Per foot

Description	1 1/4" ALU FLEXIBLE CONDUIT 200'
extra long description	AFC 5605-40-00 1-1/4 ALUM FLEX 200
Features	Reduced wall Aluminum flexible conduit is made with an aluminum alloy strip of uniform gauge for an excellent combination of strength and durability. Reduced wall flexible conduit can be used in flexible metal raceway systems for electrical power, communication cables, motor leads, listed assemblies and wire fixtures and manufactured wiring systems The Reduced Wall product must additionally meet an impact performance test. Both constructions are UL listed for use in accordance with the NEC.
Long Description	UL Reduced Wall Aluminum Type RW FAC, 5600 Series, Lightweight Reduced Wall Aluminum Flexible Conduit. Premiur aluminum alloy. Interlocking design. 1-1/4 inch Diameter, 200 Foot Reel
Product Type	1-1/4 Alum Flex 200 RL
Short Description	1-1/4 ALUM FLEX 200 RL
Special Features	Interlocking design; Corrosion resistant; Cable tray installations per NEC; Environmental air-handling space installation NEC 300.22; UL Classified 1, 2 and 3-hour Through-Penetration Fire Systems UL File R14141
anufacturer Information	
Brand	Flexible Conduit
GTIN	00077680119346
Manufacturers Part Number	5605-40-00
UPC	077680119346
xonomies, Classifications, and C	Categories
Category Description	Fuses & Fuse Accessories
Туре	Flexible Aluminum Conduit
ade Size	
Trade Size	1-1/4
ckaging	
Carton	200

0.22

44



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

For Electrical Power, Control And Communication Cables, Motor
Leads, Listed Assemblies, Listed Wire Fixtures, Manufactured
Wiring Systems
UL 1, UL 1479 File Numbers E11831 And R14141, CSA File
Number 15035, Federal Specification WW-C-566C, (Now
Superseded By UL 1), NEC 250.118(6), 300.22(C), 348, 430.123,
501.4(B)(2), 645.5