



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



ALUCPLG2 2" AI CPLG

Robroy/Ecn Korns

Catalog Number	ALUCPLG2
Manufacturer	Robroy/Ecn Korns
Description	Conduit Coupling, Threaded Female Type; Aluminum Material; Rigid Conduit Used On; 20 Standard Package; 2 Inch Trade Size; Total Length Of Thread to Vanish Point 1.0582; Effective Length 0.7565 Inch; Pitch Diameter 2.269 Inch; Thread Per Inch 11-1/2
Weight per unit	0.3500 (lbs/each)
Product Category	Aluminum

Features

Material	Aluminum
----------	----------

Descriptions

Additional Information	Total Length of Thread to Vanish Point 1.0582; Effective Length 0.7565 Inch; Pitch Diameter 2.269 Inch; Thread per Inch 11-1/2
Commodity Description	ELBOWS-COUPPLINGS-NIPPLES - ALUMINUM
Description	2" AL CPLG
extra long description	ALUMINUM MATERIAL; GALVANIZED FINISH; UL (CANADA AND US), UL 6A, CSA C22.1/C22.2, NOM APPROVAL; ANSI/NFPA 70, NEC 344, ISO 9001 APPLICABLE STANDARD; 20 PER CARTON STANDARD PACKAGE; 2 INCH TRADE SIZE; THREADED END TYPE; THREAD PER INCH 11-1/2; APPLICATION INDOOR/OUTDOOR; ALUCPLG MODEL
Long Description	CONDUIT COUPLING, THREADED FEMALE TYPE; ALUMINUM MATERIAL; RIGID CONDUIT USED ON; 20 STANDARD PACKAGE; 2 INCH TRADE SIZE; TOTAL LENGTH OF THREAD TO VANISH POINT 1.0582; EFFECTIVE LENGTH 0.7565 INCH; PITCH DIAMETER 2.269 INCH; THREAD PER INCH 11-1/2
Product Type	Conduit Coupling

Manufacturer Information

Brand	ECN-KORNS
GTIN	00784011011360
Manufacturers Part Number	ALUCPLG-2
UPC	784011011360

Taxonomies, Classifications, and Categories

Category Description	RIGID COUPLINGS
Type	THREADED FEMALE

Trade Size

Trade Size	2 INCH
------------	--------



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Packaging

Carton	1
Package	20
Standard Package	20
Weight Per each	0.35

Uses, Certifications, and Standards

Used On	RIGID CONDUIT
---------	---------------