



APPT50A 1/2IN Cond Body

Appleton/Oz Gedney

Catalog Number	APPT50A
Manufacturer	Appleton/Oz Gedney
Description	Form 85 Unilets Type T Conduit Outlet Body, Hub Size: 1/2 In, Form: 85, Length: 4-3/4 In, Height: 1.38 In, Material: Pressure Cast Aluminum, Finish: Epoxy Powder Coat, Connection: Tapered Female Threaded, Standard: UI 514A, UI 514B, UL File
Weight per unit	0.2750 (lbs/each)
Product Category	Alum

Features

connection	Tapered Female Threaded
Form	85

Material, Color, and Finish

Finish	Epoxy Powder Coat
--------	-------------------

Dimensions and Weight

Height	1.38
Hub Size	1/2
Length	4-3/4

Descriptions

Description	1/2IN COND BODY
extra long description	APP T50A 1/2 FORM 85 UNILET
Long Description	Form 85 UNILETS Type T Conduit Outlet Body, Hub Size: 1/2 IN, Form: 85, Length: 4-3/4 IN, Height: 1.38 IN, Material: Pressure Cast Aluminum, Finish: Epoxy Powder Coat, Connection: Tapered Female Threaded, Standard: UL 514A, UL 514B, UL File

Product Type	1/2 Form 85 Unilet (A)
--------------	------------------------

Special Features	Accurately tapped, tapered threads for tight, rigid joints and excellent ground continuity; Allow connections for branch runs; Connect and change direction of conduit runs; Form 85 copperfree aluminum Unilets are lightweight, self oxidizing, self-renewing and offer a high corrosion resistance; Internal volume and maximum wire capacity clearly marked on castings; Lightweight aluminum facilitates shipping, handling and installing; Make bends in conduit system; Permit access to conductors for maintenance; Provide ope
------------------	---



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Manufacturer Information

Brand	Appleton
GTIN	00781381686808
Manufacturers Part Number	T50A
UPC	781381686808

Taxonomies, Classifications, and Categories

Category Description	Fuses & Fuse Accessories
Type	Type T Conduit Outlet Body

Packaging

Carton	10
Package	50
Weight Per each	0.275

Uses, Certifications, and Standards

Application standard	For Use With Rigid Steel, Rigid Aluminum Conduit, IMC And EMT UL 514A, UL 514B, UL File Number E2527, CSA C22.2 No. 18.3, CSA 065183, NEMA FB-1
----------------------	---