

# Duraclad® Bare Armored Ground Cable

Steel Interlocked Armor. Bare Copper Ground.



## APPLICATIONS

Southwire Duraclad® Bare Armored Ground Cable is suitable for use as a grounding electrode conductor for Residential Service Systems.

## STANDARDS & REFERENCES

Southwire Duraclad® Bare Armored Ground Cable meets or exceeds the requirements of UL Standard 467.

## CONSTRUCTION

Southwire Duraclad® Bare Armored Ground Cable is constructed with a bare soft-drawn copper. A galvanized steel interlocking armor is applied over the bare conductor.



**Southwire**  
One Southwire Drive  
Carrollton, Ga. 30119 USA

greenSpec™  
RoHS Compliant



Copyright 2009, Southwire Company.  
All Rights Reserved.

®Southwire is a registered trademark  
of Southwire Company.

# Duraclad Type BAG Bare Armored Ground Cable

Conductor Size (AWG) /# of Cond.	Stranding	Outside Diameter	Approx. Weight (lbs./1000 ft.)
8/1	solid	0.460	150
6/1	solid	0.485	200
4/1	stranded	0.515	290

# Duraclad<sup>®</sup> Bare Armored Ground Cable

Steel Interlocked Armor. Bare Copper Ground.



## APPLICATIONS

Southwire Duraclad<sup>®</sup> Bare Armored Ground Cable is suitable for use as a grounding electrode conductor for Residential Service Systems.

## STANDARDS & REFERENCES

Southwire Duraclad<sup>®</sup> Bare Armored Ground Cable meets or exceeds the requirements of UL Standard 467.

## CONSTRUCTION

Southwire Duraclad<sup>®</sup> Bare Armored Ground Cable is constructed with a bare soft-drawn copper. A galvanized steel interlocking armor is applied over the bare conductor.



**Southwire**  
One Southwire Drive  
Carrollton, Ga. 30119 USA

green<sup>+</sup>Spec<sup>™</sup>  
RoHS Compliant



Copyright 2009, Southwire Company.  
All Rights Reserved.

<sup>®</sup>Southwire is a registered trademark  
of Southwire Company.

# Duraclad Type BAG Bare Armored Ground Cable

Conductor Size (AWG) /# of Cond.	Stranding	Outside Diameter	Approx. Weight (lbs./1000 ft.)
8/1	solid	0.460	150
6/1	solid	0.485	200
4/1	stranded	0.515	290