

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



BC10CG 4" C MGL CNDT BC&G

Crouse-Hinds

Catalog Number	BC10CG
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet B Mogul Conduit Body, Feraloy Iron Alloy, C Shape, Snappack Gasket and Cover, 4"
Weight per unit	39.3 (lbs/each)
Product Category	Miscellaneous

Features

dimensions 23.7500 IN X 5.2500 IN X 5.3800 IN

Material, Color, and Finish

Finish Electrogalvanized With Aluminum Acrylic Painted

Dimensions and Weight

Height	5-3/8	
Hub Size	4 in	
Length	23-3/4	

Descriptions

Description	4" C MGL CNDT BC&G
extra long description	CRS-H BC10 CG 4 NPT IRON C MOGUL BO
Features	Crouse-Hinds series mogul bodies are installed in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion
Long Description	Eaton Crouse-Hinds series Condulet B mogul conduit body, Feraloy iron alloy, C shape, SnapPack gasket and cover, 4"
Product Type	4 NPT Iron C Mogul Body Gasket Cover

Manufacturer Information

Brand	Eaton
GTIN	00662276471481
Manufacturers Part Number	BC10 CG
UPC	662276471481

Taxonomies, Classifications, and Categories

Category Description	Form 9 condulets, covers & gaskets
Туре	Mogul conduit body



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	39.3
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other

UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D