



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

1011 First Place Blvd
73099-0000, OK Yukon
Phone: 405-265-8424
Fax: 405-494-4041



BG98SA 3-1/2" to 4" Alu BLNK MGL CVR

Crouse-Hinds

| | |
|------------------|---|
| Catalog Number | BG98SA |
| Manufacturer | Crouse-Hinds |
| Description | Eaton Crouse-Hinds Series Condulet B Mogul Blank Cover, Copper-Free Aluminum, Round Neoprene Gasket, 3-1/2" or 4" |
| Weight per unit | 4.1 (lbs/each) |
| Product Category | Alum |

Features

| | |
|------------|------------------------------------|
| dimensions | 6.0000 IN X 0.7500 IN X 21.2500 IN |
|------------|------------------------------------|

Descriptions

| | |
|------------------------|---|
| Description | 3-1/2" TO 4" ALU BLNK MGL CVR |
| extra long description | CRS-H BG98 SA 3 1/2 OR 4 CST AL MOG |
| Features | Crouse-Hinds series mogul bodies are installed in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion |
| Long Description | Eaton Crouse-Hinds series Condulet B mogul blank cover, Copper-free aluminum, Round neoprene gasket, 3-1/2" or 4" |
| Product Type | 3 1/2 or 4 CST Al Mogul CVR/Gask |

Manufacturer Information

| | |
|---------------------------|---------------------------|
| Brand | EATON CROUSE-HINDS SERIES |
| GTIN | 00782274126944 |
| Manufacturers Part Number | BG98 SA |
| UPC | 782274126944 |

Taxonomies, Classifications, and Categories

| | |
|----------------------|------------------------------------|
| Category Description | Form 9 condulets, covers & gaskets |
| Type | Mogul blank cover |

Packaging

| | |
|-----------------|------|
| Carton | 1 |
| Weight Per each | 4.08 |

Uses, Certifications, and Standards

| | |
|-------------|--|
| Application | Ind Facilities & Factories - Industrial Facilities/Factories - Other |
| standard | UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D |