


ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





BISR10 1/0AWG In-Line Splice Burndy LLC

Catalog Number	BISR10
Manufacturer	Burndy LLC
Description	Aluminum In-Line Splice 14-1/0 Awa
Weight per unit	0.1300 (lbs/each)
Product Category	

Features

Conductor Size	14-1/0 AWG	
Insulation Type	Plastisol	
Material	Alullillulli	
Operating Voltage	600 V	
pallet quantity	9600	

Descriptions

1/0AWG IN-LINE SPLICE
BUR BISR1/0 1/0-14 IN-LINE SPLICE
Aluminum In-Line Splice, 14-1/0 AWG.
SPLICE REDUCER
Features: Clear Plastisol Covered AL6061-T6 Aluminum Body:
Saves Time, Lowers Installation Costs, Eliminates Taping, Clear
Plastisol: Allows Visual Confirmation That Conductor Is Properly
Inserted, Oxide Inhibitor Pre-Installed: Inhibits Moisture And
Contaminants From Entering The Contact Area, Range-Taking:
Reduces Number Of Connectors Carried In Inventory, UL486B
Listed, Dual-Rated AL9CU For Any Stranded Copper Or Stranded
Aluminum Applications, 600 Volt, 90 DEG C, Wire Entry: In-Line,

Manufacturer Information

Brand	BURNDY
GTIN	00781810134115
Manufacturers Part Number	BISR1/0
UPC	781810134115

Torque: 50 IN-LB,

Taxonomies, Classifications, and Categories

Category Description	Comp & Mech Lugs and Butt Splices
Туре	BISR

Packaging

Carton	1	
Package	100	
Weight Per each	0.13	

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	For Indoor Use Only, Copper Or Stranded Aluminum
standard	UL 486A-486B
Temperature Rating	194