

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



BIT4 Burndy Bit4 Burndy LLC

Catalog Number	BIT4
Manufacturer	Burndy LLC
Description	Aluminum Multiple Tap Connector, Clear Insulated, 2 Port, 1 Sided Entry, 14-4 Awg, Al/Cu Rated.
Weight per unit	0.0280 (lbs/each)
Product Category	Large Terminals & Connectors
Features	
Conductor Size	14-4 AWG
Insulation Type	Plastisol
Material	Aluminum
Operating Voltage	600 V
Descriptions	
Description	BURNDY BIT4
extra long description	BUR BIT4 14-4 ONE SIDED UNITAP,1.08
Long Description	Aluminum Multiple Tap Connector, Clear Insulated, 2 Port, 1 Sided Entry, 14-4 AWG, Al/Cu Rated.
Product Type	RUN/TAP
Special Features	Features: Clear Plastisol Covered AL6061-T6 Aluminum Body: Saves Time, Lowers Installation Costs, Eliminates Taping, Clear Plastisol: Allows Visual Confirmation That Conductor Is Properly Inserted, Oxide Inhibitor Pre-Installed: Inhibits Moisture And Contaminants From Entering The Contact Area, Range-Taking: Reduces Number Of Connectors Carried In Inventory, Torque: 45 IN-LB, Wire Entry: 1 or 2, Hex Size (key): 1/8 IN, Conductor Size (run - Range): 14 - 4 AWG, Wire Strip Length: 5/8 IN, Number Of Ports: 2,
Manufacturer Information	
Brand	BURNDY
GTIN	00781810134146
Manufacturers Part Number	BIT4
sub brand	UNITAP
UPC	781810134146
Taxonomies, Classifications, and (
	Fuses & Fuse Accessories
Туре	BIT
5.	F
Packaging Carton	1
Weight Per each	0.028



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	For Indoor Use Only, Copper Or Stranded Aluminum
standard	UL 486A-486B
Temperature Rating	90 °C