Class CC, Type M and Class G Fuse Blocks

BC Series



Specifications

Description: Class CC fuse blocks for use with Class CC fuses (Bussmann LP-CC, KTK-R, and FNQ-R).

Dimensions: See Data Sheet 1105

Poles: 1 to 3
Ratings:

Volts: — 600V Amps: — 1/10-30A

SCCR: - 200kA RMS Sym.

Agency Information: CE, UL Listed (Guide IZLT, File E14853), CSA (Class

6225-01, File 47235)

Flammability Rating: UL 94V0

DIN-Rail Adapters: See page 413 for

DRA-1 & DRA-2

Catalog Numbers

Terminal Type						
Screw	Screw with Quick Connect*	Pressure Plate	Pressure Plate w/ Quick Connect*	Box Lug	Poles	
BC6031S	BC6031SQ	BC6031P	BC6031PQ	BC6031B	1	
BC6032S	BC6032SQ	BC6032P	BC6032PQ	BC6032B	2	
BC6033S	BC6033SO	BC6033P	BC6033PO	BC6033B	3	

Data Sheet: 1105

BCCM Series

Description: 3-pole fuse block for use with (2) Class CC fuses and (1) ½" x 1½"

Catalog Numbers

Catalog	Terminal
Numbers	Туре
BCCM6033SQ	Screw with Quick-Connect*
BCCM6033PQ	Pressure Plate w/Quick-Connect*
*Ouick-connect termina	I rated for 20A may

Recommended Cover Puller

- PF1-WH (White)
- PF1-BK (Black)

BM Series Type M



Specifications

Description: Supplementary fuse blocks for use with any ½" x 1½" fuses (Bussmann KTK, PVM, FNQ, FNM, BAF, PV, and AGU).

Dimensions: See Data Sheet 1104

Poles: 1 to 3

DIN-Rail Adapters: See page 413

for DRA-1 & DRA-2

Ratings:

Volts: - 600Vac/dc Amps: - 1/10-30A

SCCR:- 10kA RMS Sym.

Agency Information: CE, UL Recognized (Guide IZLT2, File E14853), CSA (Class 6225-01, File 47235).

Flammability Rating: UL 94V0.

Catalog Numbers

Terminal Type					
Screw Pressure with Plate w/ Quick Quick Connect* Connect*		Box Lug	Poles		
BM6031SQ	BM6031PQ	BM6031B	1		
BM6032SQ	BM6032PQ	BM6032B	2		
BM6033SQ	BM6033PQ	BM6033B	3		

Recommended Cover Puller

- PF1-WH (White)
- PF1-BK (Black)

BG & G Series



Specifications

Description: Class G fuse blocks for use with Class G fuses (Bussmann SC). **Dimensions:** See Data Sheet 1106

Poles: 1 to 3

Ratings:

Volts: — 600Vac/dc (0-20A) — 480Vac/dc (25-60A)

Amps: - 1-60A (See Catalog Numbers

table)

SCCR: - 100kA RMS Sym.

Agency Information: CE, UL Listed 35-60A (Guide IZLT, File E14853), UL Recognized 1-30A, (Guide IZLT2, File E14853), CSA (Class 6225-01, File 47235).

DIN-Rail Adapters: See page 413 for

DRA-1 & DRA-2.

Catalog Numbers

_							
Terminal Type							
Screw with Quick Connect*	Pressure Plate w/ Quick Connect*	Box Lug	Box Lug w/retaining clip	Amps	Poles		
BG3011SQ	BG3011PQ	BG3011B	_		1		
BG3012SQ	BG3012PQ	BG3012B	_	1-15	2		
BG3013SQ	BG3013PQ	BG3013B	_		3		
BG3021SQ	BG3021PQ	BG3021B	_		1		
BG3022SQ	BG3022PQ	BG3022B	_	20	2		
BG3023SQ	BG3023PQ	BG3023B	_		3		
BG3031S	BG3031P	BG3031B	_		1		
BG3032S	BG3032P	BG3032B	_	25-30	2		
BG3033S	BG3033P	BG3033B	_		3		
_	_	_	G30060-1CR		1		
	_		G30060-2CR	35-60	2		
_		G30060-3C	G30060-3CR		3		

Recommended Cover Puller

- PF1-WH (White)
- PF1-BK (Black)

Data Sheet: 1104

Data Sheet: 1106

Class CC, Type M and Class G Fuse Blocks

BC Series



Specifications

Description: Class CC fuse blocks for use with Class CC fuses (Bussmann LP-CC, KTK-R, and FNQ-R).

Dimensions: See Data Sheet 1105

Poles: 1 to 3
Ratings:

Volts: — 600V Amps: — 1/10-30A

SCCR: - 200kA RMS Sym.

Agency Information: CE, UL Listed (Guide IZLT, File E14853), CSA (Class

6225-01, File 47235)

Flammability Rating: UL 94V0

DIN-Rail Adapters: See page 413 for

DRA-1 & DRA-2

Catalog Numbers

Terminal Type						
Screw	Screw with Quick Connect*	Pressure Plate	Pressure Plate w/ Quick Connect*	Box Lug	Poles	
BC6031S	BC6031SQ	BC6031P	BC6031PQ	BC6031B	1	
BC6032S	BC6032SQ	BC6032P	BC6032PQ	BC6032B	2	
BC6033S	BC6033SO	BC6033P	BC6033PO	BC6033B	3	

Data Sheet: 1105

BCCM Series

Description: 3-pole fuse block for use with (2) Class CC fuses and (1) ½" x 1½"

Catalog Numbers

Catalog	Terminal
Numbers	Туре
BCCM6033SQ	Screw with Quick-Connect*
BCCM6033PQ	Pressure Plate w/Quick-Connect*
*Ouick-connect termina	I rated for 20A may

Recommended Cover Puller

- PF1-WH (White)
- PF1-BK (Black)

BM Series Type M



Specifications

Description: Supplementary fuse blocks for use with any ½" x 1½" fuses (Bussmann KTK, PVM, FNQ, FNM, BAF, PV, and AGU).

Dimensions: See Data Sheet 1104

Poles: 1 to 3

DIN-Rail Adapters: See page 413

for DRA-1 & DRA-2

Ratings:

Volts: - 600Vac/dc Amps: - 1/10-30A

SCCR:- 10kA RMS Sym.

Agency Information: CE, UL Recognized (Guide IZLT2, File E14853), CSA (Class 6225-01, File 47235).

Flammability Rating: UL 94V0.

Catalog Numbers

Terminal Type					
Screw Pressure with Plate w/ Quick Quick Connect* Connect*		Box Lug	Poles		
BM6031SQ	BM6031PQ	BM6031B	1		
BM6032SQ	BM6032PQ	BM6032B	2		
BM6033SQ	BM6033PQ	BM6033B	3		

Recommended Cover Puller

- PF1-WH (White)
- PF1-BK (Black)

BG & G Series



Specifications

Description: Class G fuse blocks for use with Class G fuses (Bussmann SC). **Dimensions:** See Data Sheet 1106

Poles: 1 to 3

Ratings:

Volts: — 600Vac/dc (0-20A) — 480Vac/dc (25-60A)

Amps: - 1-60A (See Catalog Numbers

table)

SCCR: - 100kA RMS Sym.

Agency Information: CE, UL Listed 35-60A (Guide IZLT, File E14853), UL Recognized 1-30A, (Guide IZLT2, File E14853), CSA (Class 6225-01, File 47235).

DIN-Rail Adapters: See page 413 for

DRA-1 & DRA-2.

Catalog Numbers

_							
Terminal Type							
Screw with Quick Connect*	Pressure Plate w/ Quick Connect*	Box Lug	Box Lug w/retaining clip	Amps	Poles		
BG3011SQ	BG3011PQ	BG3011B	_		1		
BG3012SQ	BG3012PQ	BG3012B	_	1-15	2		
BG3013SQ	BG3013PQ	BG3013B	_		3		
BG3021SQ	BG3021PQ	BG3021B	_		1		
BG3022SQ	BG3022PQ	BG3022B	_	20	2		
BG3023SQ	BG3023PQ	BG3023B	_		3		
BG3031S	BG3031P	BG3031B	_		1		
BG3032S	BG3032P	BG3032B	_	25-30	2		
BG3033S	BG3033P	BG3033B	_		3		
_	_	_	G30060-1CR		1		
	_		G30060-2CR	35-60	2		
_		G30060-3C	G30060-3CR		3		

Recommended Cover Puller

- PF1-WH (White)
- PF1-BK (Black)

Data Sheet: 1104

Data Sheet: 1106