

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

BR160 Type BR BRKR 60A/1 Pole 120/240V 10K Eaton Corp

Catalog Number	BR160
Manufacturer	Eaton Corp
Description	Eaton BR Thermal Magnetic Circuit Breaker, Type BR 1-Inch Plug-On Circuit Breaker, 60 A, 10 Kaic, Single-Pole, 120/240V, BR, #4-1/0 Awg Cu/Al, BR, Type BR Loadcenters
Weight per unit	0.3000 (lbs/each)
Product Category	1 Pole Standard Trip Plug-In
Features	
dimensions	3.0000 IN X 1.0000 IN X 3.0000 IN
interrupt rating	10 kAIC
Poles	Single-pole
Voltage Rating	120/240 V
Descriptions	
Description	TYPE BR BRKR 60A/1 POLE 120/240V 10K
extra long description	ETN BR160 Type BR Breaker 60A/1 Pol
Features	Eaton's residential BR Circuit Breakers are used in load centers, panelboards, or similar devices. They are made for a wide range of applications and include: BR 1" circuit breakers and accessories for BR-style load centers; arc fault circuit interrupters (AFCI); and ground fault circuit interrupters (GFCI).
Long Description	Eaton BR thermal magnetic circuit breaker, Type BR 1-Inch plug-on circuit breaker, 60 A, 10 kAIC, Single-pole, 120/240V, BR, #4-1/0 AWG Cu/AI, BR, Type BR Loadcenters
Product Type	Type BR Breaker 60A/1 Pole 120/240V 10K
Manufacturer Information	5.
Brand	EATON CUTLER-HAMMER
GTIN	00786676362351
Manufacturers Part Number	BR160
UPC	786676362351
Taxonomies, Classifications, and	Categories
Category Description	Loadcontor Diug In Prockers and Assessaries
Type	Thermal magnetic circuit breakers
Packaging	5
Carton	1
.f.W	

0.3

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Generation - Renewable Energy - Alternative EnergyMarine
	Vessels and Equipment - Marine Vessels and Equipment -
	OtherOtherGeneration - Conventional Energy - Conventional
	EnergyDatacenters - IT Space: CI and Hyper Converged
standard	UL 489, Federal Specifications Classification W-C375