

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

## BR230SURCS Type BR Surge BRKR 30A/2 Pole 120/240V 10K

Eaton Corp	
Catalog Number	BR230SURCS
Manufacturer	Eaton Corp
Description	Eaton BR Residential Surge Breaker, Two-Pole, 30 A, 10 Ka Nominal Discharge, 36 Ka Surge Current
Weight per unit	1.0 (lbs/each)
Product Category	2 Pole Standard Trip Plug-In
Features	
amperage rating	30 A
dimensions	6.5000 IN X 3.5000 IN X 2.5000 IN
Descriptions	
Description	TYPE BR SURGE BRKR 30A/2 POLE 120/240V 10K
extra long description	ETN BR230SUR BR SURGE BRKR 30A/2 PO
Features	Eaton offers a comprehensive family of surge products for use at service entrances. These products can help protect sensitive electronics against the damaging effects of surges. Due to the evolution of electronics and microprocessors in the home, there is a continuous challenge to provide quality (clean) power for electronic loads such as appliances, computers/home office and entertainment systems. Surges caused by lightning, utility grid switching and other sources travel on current carrying conductors t
Long Description	Eaton BR residential surge breaker, Two-pole, 30 A, 10 kA nominal discharge, 36 kA surge current
Product Type	BR Surge BRKR 30A/2 Pole 120/240V 10K
Manufacturer Information	
Brand	Eaton
GTIN	00786685546063
Manufacturers Part Number	BR230SUR
UPC	786685546063
Taxonomies, Classifications, and (	Categories
Category Description	SURGE SUPRESSION PRODUCTS
Туре	Surge breaker
Availability Status	Inactive
Packaging Carton	1

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications,	and Standards
-----------------------	---------------

i iudi us
Generation - Conventional Energy - Conventional EnergyMarine
Vessels and Equipment - Marine Vessels and Equipment -
OtherGeneration - Renewable Energy - Alternative
EnergyDatacenters - IT Space: CI and Hyper ConvergedOther
UL 489,UL 1449