

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

BR4242L400R 1PH 400A Mlo 42/42 Cir. Al Bus Nema 3R Eaton Corp

Eaton Corp	
Catalog Number	BR4242L400R
Manufacturer	Eaton Corp
Description	Eaton BR Main Lug Loadcenter, With Flush or Nema Type 3R Cover, Outdoor, 400 A, 46, Aluminum, Nema 3R, 42 Circuits, 42 Spaces, Four-Wire, Three-Phase, Type BR 1-Inch Breakers, 208Y/120, 240V, (1) 250–750 Kcmil or (2) #3/0–250 Kcmil
Weight per unit	67.0 (lbs/each)
Product Category	Single Phase Main Breaker Load
Features	
amperage rating	400 A
Cover Type	Cover included
dimensions	6.3800 IN X 16.3100 IN X 54.0000 IN
interrupt rating	25 kAIC
number of spaces	42
Phase	Single-phase
Descriptions	
Description	1PH 400A MLO 42/42 CIR. AL BUS NEMA 3R
extra long description	ETN BR4242L400R Eaton BR main lug l
Features	Eaton's BR 1-inch main lug load center is used when a sub-panel is needed to add circuits to an existing service. BR load centers house the branch circuit breakers and the wiring required to distribute power to individual circuits.
Long Description	Eaton BR main lug loadcenter, With flush or NEMA type 3R cover, Outdoor, 400 A,46, Aluminum, NEMA 3R,42 Circuits, 42 Spaces, Four-wire, Three-phase, Type BR 1-inch breakers, 208Y/120, 240V, (1) 250–750 kcmil or (2) #3/0–250 kcmi
Product Type	Eaton BR Main Lug Loadcenter
Manufacturer Information	
Brand	Eaton
GTIN	00786685924007
Manufacturers Part Number	BR4242L400R
UPC	786685924007
Taxonomies, Classifications, and	Categories
Category Description	104505117550 - 001/550
Туре	Main lug loadcenter
Packaging Carton	1
61776 B.T. 46	

67



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies, Panels and EOEMs
Mounting	SURFACE
standard	UL 67,UL 50