

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



### **BRNSURGE Type BR 2 Pole Surge Arrester** *Eaton Corp*

Eaton Corp	
Catalog Number	BRNSURGE
Manufacturer	Eaton Corp
Description	Eaton Type BR Circuit Breaker Surge Protective Device, Two Pole,
	Surge Protective Device
Weight per unit	1.0 (lbs/each)
Product Category	Distribution Equipment
Features	
dimensions	3.6000 IN X 3.5000 IN X 2.2500 IN
<b>Dimensions and Weight</b>	
Depth	3.6
Height	2.25
Width	3.5
Descriptions	
Description	TYPE BR 2 POLE SURGE ARRESTER
extra long description	EWD BRNSURGE Type BR 2 pole Surge A
Features	Eaton offers a comprehensive family of surge products for use at
	service entrances. These products can help protect sensitive
	electronics against the damaging effects of surges. Due to the evolution of electronics and microprocessors in the home, there
	is a continuous challenge to provide quality (clean) power for
	electronic loads such as appliances, computers/home office and
	entertainment systems. Surges caused by lightning, utility grid
	switching and other sources travel on current carrying
	conductors t
Long Description	Eaton Type BR circuit breaker surge protective device, Two Pole,
	Surge Protective Device
Product Type	Type BR 2 Pole Surge Arrester
Manufacturer Information	
Brand	Eaton
GTIN	00786689353667
Manufacturers Part Number	BRNSURGE
UPC	786689353667
Taxonomies, Classifications, and C	Categories
Category Description	5 U.O. I. D. I. (A501/0501)

#### Taxo

Category Description	Fault Sensing Breakers (AFCI/GFCI)
Туре	Plug on module surge protection device

#### **Availability**

Status Inactive



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	1
Uses, Certifications, and Standards	
Application	OtherResidential Bldgs & Facilities - Residential Bldgs & Facilities -
	Other
standard	cUL Certified,UL 1449