

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## **BUB4 1-1/4" Bub Conduit Body** *Crouse-Hinds*

Catalog Number	BUB4
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet B Mogul Conduit Body, Feraloy Iron Alloy, Ub Shape, 1-1/4"
Weight per unit	3.5 (lbs/each)
Product Category	

#### **Features**

dimensions 9.3100 IN X 2.1900 IN X 3.1900 IN

#### Material, Color, and Finish

Finish Electrogalvanized With Aluminum Acrylic Painted

#### **Dimensions and Weight**

Height	3-3/16	
Hub Size	1-1/4 111	
Length	9-5/16	
Width	2-3/16	

### **Descriptions**

Description	1-1/4" BUB CONDUIT BODY
extra long description	CRS-H BUB4 1-1/4 NPT IRON UB MOGUL
Features	Crouse-Hinds series mogul bodies are installed in conduit systems to act as pull outlets for conductors that are stiff due to large size or type of insulation. Mogul bodies provide longer openings needed when pulling large conductors and prevent sharp bends and kinks during installation. Mogul conduit bodies are manufactured in trade sizes 1/2" to 6" and are available in Feraloy iron alloy and copper-free aluminum. Our iron alloy bodies are available with a hot dip galvanized finish for added corrosion
Long Description	Eaton Crouse-Hinds series Condulet B mogul conduit body, Feraloy iron alloy, UB shape, 1-1/4"
Product Type	1-1/4 NPT Iron Ub Mogul Body

#### **Manufacturer Information**

Brand	EATON CROUSE-HINDS SERIES
GTIN	00782274108407
Manufacturers Part Number	BUB4
UPC	782274108407

## **Taxonomies, Classifications, and Categories**

Category Description	FORM 7, 8, CONDULETS, COVERS, & GASKETS
Туре	Mogul conduit body



# ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

	•		

Packaging		
Carton	1	
Package	2	
Weight Per each	3.5	
Uses, Certifications, and Stan	dards	
Application	Ind Facilities & Factories - Industrial Facilities/Factories - Other	
standard	UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D	