



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## **C1.5BL6 1-1/2 Black CVR P/FT** *Panduit Corporation*

Catalog Number	C1.5BL6
Manufacturer	Panduit Corporation
Description	The C1.5BL6 PVC Flush Wiring Duct Cover Features A Non-Slip, Liner to Prevent Cover Slide. Designed With The User In Mind, The Cover Is Easy to Install and Remove. The General-Purpose Lead-Free PVC Material Is Suitable For Use In Indoor Applications. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). 0.35" X 1.75" (8.9 MM X 44.5 MM) and 6' (1.83 M) Long. Color Black.
Weight per unit	0.5300 (lbs/each)
Product Category	Ducts, Raceways, Runways, Tray

### **Features**

connection	Snap-on
media	Yes

### **Material, Color, and Finish**

Color	Black
-------	-------

### **Dimensions and Weight**

Length	NA
Width	1.75

### **Descriptions**

Description	1-1/2 BLACK CVR P/FT
extra long description	PAN C1.5BL6 Panduct® C1.5BL6 Flush
Long Description	The C1.5BL6 PVC Flush Wiring Duct Cover features a non-slip, liner to prevent cover slide. Designed with the user in mind, the cover is easy to install and remove. The general-purpose lead-free PVC material is suitable for use in indoor applications. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). 0.35" x 1.75" (8.9 mm x 44.5 mm) and 6' (1.83 m) long. Color Black.
Product Type	Panduct® C1.5BL6 Flush Duct Cover

### **Manufacturer Information**

Brand	PANDUIT
GTIN	00074983230594
Manufacturers Part Number	C1.5BL6
UPC	074983230594



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Taxonomies, Classifications, and Categories

Category Description	WIRE DUCT AND COVERS
Type	Flushed Duct Cover

## Packaging

Carton	120
Weight Per each	0.53

## Uses, Certifications, and Standards

Application	Cover for Wiring Duct
standard	CE Compliant;CSA Certified;Flammability Ratings: UL94 V-0;RoHS Compliant;UL Recognized