



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4406 Highway 28 East  
71360-0000, LA Pineville  
Phone: 318-767-0900  
Fax: 318-767-0010



## C29 3/4" Al C MRK 9 CNDT Body *Crouse-Hinds*

Catalog Number	C29
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Condulet Mark 9 Conduit Outlet Body, Copper-Free Aluminum, C Shape, 3/4"
Weight per unit	0.4200 (lbs/each)
Product Category	Alum

### Features

dimensions	5.3400 IN X 1.5600 IN X 1.6300 IN
------------	-----------------------------------

### Material, Color, and Finish

Finish	Untreated
--------	-----------

### Dimensions and Weight

Height	1-5/8
Hub Size	3/4 in
Length	5-11/16
Width	1-9/16

### Descriptions

Description	3/4" AL C MRK 9 CNDT BODY
extra long description	CRS-H C29 3/4 NPT CST AL C MARK 9 C
Features	Mark 9 copper-free aluminum conduit bodies, covers and gaskets from Eaton's Crouse-Hinds Division are used in conduit systems to act as pull outlets for conductors being installed, provide openings for making splices and taps in conductors, make 90 degree bends in conduit runs, and provide for access to conductors for maintenance and future system changes. Mark 9 bodies are offered in seven different shapes, and they provide more room for heavier conductors.
Long Description	Eaton Crouse-Hinds series Condulet Mark 9 conduit outlet body, Copper-free aluminum, C shape, 3/4"
Product Type	3/4 NPT CST Al C Mark 9 CNDT Body

### Manufacturer Information

Brand	Crouse-Hinds
GTIN	00782274123004
UPC	782274123004

### Taxonomies, Classifications, and Categories

Type	Conduit outlet body
------	---------------------



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

4406 Highway 28 East  
71360-0000, LA Pineville  
Phone: 318-767-0900  
Fax: 318-767-0010

## Packaging

Carton ..... 5

Weight Per each ..... 0.42

## Uses, Certifications, and Standards

Application ..... Ind Facilities & Factories - Industrial Facilities/Factories - Other

standard ..... UL 514B, CSA C22.2, FEDERAL SPECIFICATION W-C-586D