



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3205 Axtell  
88101-0000, NM Clovis  
Phone: 575-742-2504  
Fax: 575-742-2508

## C3WH6 3-In WHT CVR P/FT *Panduit Corporation*

Catalog Number	C3WH6
Manufacturer	Panduit Corporation
Description	The C3WH6 PVC Flush Wiring Duct Cover Features A Non-Slip, Liner to Prevent Cover Slide. Designed With The User In Mind, The Cover Is Easy to Install and Remove. The General-Purpose Lead-Free PVC Material Is Suitable For Use In Indoor Applications. UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use Temperature Up to 122°F (50°C). 0.37" X 3.25" (9.4 MM X 82.6 MM) and 6' (1.83 M) Long. Color White.
Weight per unit	0.0083 (lbs/each)
Product Category	Wiring Duct & Accessories

### Features

connection	Snap-on
media	Yes

### Material, Color, and Finish

Color	White
-------	-------

### Dimensions and Weight

Length	NA
Width	3.25

### Descriptions

Description	3-IN WHT CVR P/FT
extra long description	PAN C3WH6 Panduct® C3WH6 Flush Duct
Long Description	The C3WH6 PVC Flush Wiring Duct Cover features a non-slip, liner to prevent cover slide. Designed with the user in mind, the cover is easy to install and remove. The general-purpose lead-free PVC material is suitable for use in indoor applications. UL 94 flame class of V-0 with a UL recognized continuous-use temperature up to 122°F (50°C). 0.37" x 3.25" (9.4 mm x 82.6 mm) and 6' (1.83 m) long. Color White.
Product Type	Panduct® C3WH6 Flush Duct Cover

### Manufacturer Information

Brand	PANDUIT
GTIN	00074983231225
Manufacturers Part Number	C3WH6
UPC	074983231225



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3205 Axtell  
88101-0000, NM Clovis  
Phone: 575-742-2504  
Fax: 575-742-2508

## Taxonomies, Classifications, and Categories

Category Description	Panduit & Wiremold Metallic & Non-Metallic Raceways
Type	Flushed Duct Cover

## Availability

minimum qty	6
-------------	---

## Packaging

Carton	120
Weight Per foot	0.0083

## Uses, Certifications, and Standards

Application	Cover for Wiring Duct
standard	CE Compliant;CSA Certified;Flammability Ratings: UL94 V-0;RoHS Compliant;UL Recognized