

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





C3WH6 3-In WHT CVR P/FTPanduit Corporation

00)4/11/
C3WH6
Panduit Corporation
The C3WH6 PVC Flush Wiring Duct Cover Features A Non-Slip, Liner to Prevent Cover Slide. Designed With The User In Mind,
The Cover Is Easy to Install and Remove. The General-Purpose
Lead-Free PVC Material Is Suitable For Use In Indoor Application
UI 94 Flame Class Of V-0 With A UI Recognized Continuous-Use
Temperature Up to 122°F (50°C). 0.37" X 3.25" (9.4 MM X 82.6
MM) and 6' (1.83 M) Long. Color White.
0.0083 (lbs/each)
Wiring Duct & Accessories
Snap-on
PVC
Yes
White
NA
3,25
3-IN WHT CVR P/FT
PAN C3WH6 Panduct® C3WH6 Flush Duct
The C3WH6 PVC Flush Wiring Duct Cover features a non-slip,
liner to prevent cover slide. Designed with the user in mind, the
cover is easy to install and remove. The general-purpose
lead-free PVC material is suitable for use in indoor applications.
UL 94 flame class of V-0 with a UL recognized continuous-use
temperature up to 122°F (50°C). 0.37" x 3.25" (9.4 mm x 82.6
mm) and 6' (1.83 m) long. Color White. Panduct® C3WH6 Flush Duct Cover
Tanidact Covino Hasii Duct Covei
DANIDUIT
PANDIII
PANDUIT 00074983231225
00074983231225 C3WH6



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	gories
Category Description	Panduit & Wiremold Metallic & Non-Metallic Raceways
Туре	Flushed Duct Cover
Availability minimum qty	6
Packaging	
Carton	120
Weight Per foot	0.0083
Uses, Certifications, and Standards	
Application	Cover for Wiring Duct
standard	UL Recognized; Flammability Ratings: UL94 V-0; CSA Certified; CE Compliant; RoHS Compliant