

## ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Type

## C4 #4 Cu Long Barrel Compression Butt Splice

Nsi Industries	Trei Compression butt spiice
Catalog Number	C4
Manufacturer	Nsi Industries
Description	Compression Splice Connector, #6 Awg Conductor Size, #4 Awg Conductor Size, Non-Insulated, Copper Conductor Material, Gray Insulation Color, 2 Conductors, +90 °C Operating Temperature, 1.752 In Overall Length, Compression Terminal, 600 V, 0.052 LB/Ea
Weight per unit	0.0520 (lbs/each)
Product Category	Large Terminals & Connectors
Features  Material  Number of Conductors	Copper 2
Poles	1
Voltage Rating Warranty	AVEAD
•	I TEAR
Material, Color, and Finish Color	Cray
Finish	Gray Tin Plated
	Titi Tatou
Dimensions and Weight Size	L=1.75 - OD=.340 - ID=.250
Descriptions	L 11.70 00 10 10 12 1200
Description	#4 CU LONG BARREL COMPRESSION BUTT SPLICE
extra long description	NSI C-4 4 AWG Copper Long Barrel Sp
Features	Long Barrel TinnedCopperSplice4 AWG Long Barrel Tinned CopperSplices is a type of copper compression connector that is produced from high conductivity copper tubing. They are tin-plated to provide corrosion resistance and are marked with die index and color coded for easy reference. Listed for 35KV maximum when properly installed.
Manufacturer Information	
GTIN	00662381037510
UPC	662381037510
Taxonomies, Classifications, and	Categories
	Comp & Mech Lugs and Butt Splices
T	Lang Daniel CH Calles

Long Barrel - CU Splice



## Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

a				

Carton	1
Package	100
Weight Per each	0.052

## Uses, Certifications, and Standards

Application	Terminate, Splice, Tap Power Connectors
environmental conditions	90 C
standard	UL486A/B, UL467 (8 AWG -3/0 AWG)
Temperature Rating	90 C