

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

CCV2175 CCV BRKR 175A/2 Pole 120/240V 10K *Eaton Corp*

Catalog Number	CCV2175	
Manufacturer	Eaton Corp	
Description	Eaton Type CCV Tenant Main Circuit Breaker, Tenant Main Circui Breaker, 175 A, 10 Kaic, Two-Pole, 120/240 V, #2/0 Awg-300 Kcmil Cu/Al, CCV, Type Ecc Unit Enclosures	
Weight per unit	2.5 (lbs/each)	
Product Category	Main Circuit Breaker Modules	
eatures		
dimensions	8.0000 IN X 4.5000 IN X 5.5000 IN	
interrupt rating	10 kAIC	
Poles	Two-pole	
Voltage Rating	120/240 V	
escriptions		
Description	CCV BRKR 175A/2 POLE 120/240V 10K	
extra long description	ETN CCV2175 CCV BREAKER 175A/2 POLE	
Features	Eaton's main circuit breakers are used in a variety of applications including the main or emergency disconnect on the outside of a house, a tenant main breaker in group metering stacks and feed-through lug blocks specifically designed for sub-feeding from an existing panel. Main breakers are available with a variety of accessories including shunt trip, bell alarms and auxiliary switches.	
Long Description	Eaton Type CCV Tenant Main Circuit Breaker, Tenant main circuit breaker, 175 A, 10 kAIC, Two-pole, 120/240 V, #2/0 AWG-300 kcmil Cu/AI, CCV, Type ECC unit enclosures	
Product Type	CCV Breaker 175A/2 Pole 120/240V 10K	
Manufacturer Information		
Brand	Eaton	
GTIN	00786685368511	
Manufacturers Part Number	CCV2175	
UPC	786685368511	
axonomies, Classifications, and (Categories	
Category Description		
Туре	Tenant main breaker	
Packaging		
Carton	1	

2.5

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications,	and Standards
-----------------------	---------------

Marine Vessels and Equipment - Marine Vessels and Equipment -
OtherOtherGeneration - Conventional Energy - Conventional
EnergyDatacenters - IT Space: CI and Hyper
ConvergedGeneration - Renewable Energy - Alternative Energy
UL 489