



Blackburn



NOTE:

- 1.- ADD SUFFIX "P" FOR TIN PLATED VERSION.
- 2.- CONNECTORS APPROVED FOR USE WITH COPPER CLAD STEEL.
- 3.- MADE OF PURE ELECTROLYTIC COPPER
- 4.- STD COMPRESSION TOOLS AND DIES
- 5.- FULL TAB LENGTH

CF4040-1	-	4/0		-	4/0		.528	.414	.528	.414	2.25	1.48	1 1/8	-	-	-	BKB	BKB	BKB	BKB
		D	D		D	D														
CF4010-1	-	4/0		-	1/0		.528	.414	.373	.292	1.99	1.42	1 1/8	-	-	-	BKB	BKB	BKB	BKB
CF402-1	-	4/0		2	4												.528	.414	.258	.204
CF2020-1	-	2/0		-	2/0		.419	.368	.414	.292	1.74	1.22	7/8	-	-	-				
CF202-1	-	2/0		2	4												.419	.368	.258	.204
CF1010-1	-	1/0		-	1/0		.373	.292	.373	.292	1.61	1.05	27/32	-	-	-				
CF102-1	-	1/0		2	4												.373	.292	.258	.162
CFS22-1	2	4	2	4	.258	.204	.258	.162	1.01	.842	13/16	K	K	W-KK	W-KK	BKT				
CF22-1	2	4	2	4	.258	.204	.258	.204	1.16	.813	13/16	K	K	W-KK	-	-	-	-	BKT	
CFS44-1	4	6	4	8	.204	.162	.204	.128	.864	.743	13/16	B,T, 5/8	B,T, 5/8	W-KB W-BG	BKT	BKT	BKT U-BG	BKT U-BG		
CF44-1	4	6	4	6	.204	.162	.204	.128	.971	.729	13/16	B,T, 5/8	B,T, 5/8	W-KB W-BG	BKT	B	BKT U-BG	BKT U-B		
CAT No.	SOL.	STR.	SOL.	STR.	MAX.	MIN	MAX	MIN	X	Y	LENGTH	OD 58	TYPE O	MD SERIES	JB12A JB12B	H SERIES	Y-35	TBM15 Y42/Y46		
	MAIN		TAP		MAIN		TAP													
	STANDARD CONDUCTOR				DIAMETER (IN)															
	CONDUCTOR RANGE																			
												MECHANICAL TOOLS (3 INDENTS)				HYDRAULIC TOOLS (1 INDENT)				
												INSTALLATION INFORMATION								

GENERAL NOTES

1. ALL DIMENSIONS ARE FOR REFERENCE ONLY.
2. DIMENSIONS IN BRACKETS [] ARE IN METRIC UNITS.

REVISIONS

1. SEE ERN (2012676) FOR APPROVAL SIGNATURES & RELEASE DATE.
PROJECT NO: BM400648

Thomas & Betts
www.tnb.com

DESCRIPTION:

COPPER H-TAP

ORIGINAL PROJECT NO / (ERN NO)

SHEET NO:

REV. NO:

DRAWING NO:

BC55900 / (2010958)

1 OF 1

1

WSD-000520