ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

CH150 1P 50A 120V Breaker
Eaton Corp

Catalog Number	CH150
Manufacturer	Eaton Corp
Description	Eaton Type CH 3/4-Inch Standard Circuit Breaker, Type CH 3/4-Inch Standard Circuit Breaker, 50 A, 10 Kaic, Single-Pole, 120/240V, CH, #14-2 Awg Cu/Al, CH, Type CH Loadcenters
Weight per unit	0.2800 (lbs/each)
Product Category	1 Pole Standard Trip Plug-In

Features

interrupt rating	10 kAIC
Poles	Single-pole
Voltage Rating	120/240 V

Dimensions and Weight

Height	3 in
Length	3.5 in
Width	5 in

Descriptions

Description	1P 50A 120V BREAKER
extra long description	ETN CH150 CH15096-4604-11Type CH Br
Features	Eaton's residential CH circuit breakers provide premium overload protection. The Type CH circuit breakers trip to the OFF position, eliminating nuisance callbacks. The CHF family also includes a trip flag to differentiate between a trip and the breaker being turned off. The thermal-magnetic trip curve avoids nuisance tripping on mild overloads while reacting almost instantaneously to severe short-circuit conditions. Multiple breakers have an internal common trip connection to operate all poles simultaneous
Long Description	Eaton Type CH 3/4-Inch Standard Circuit Breaker,Type CH 3/4-Inch standard circuit breaker,50 A,10 kAIC,Single-pole,120/240V,CH,#14-2 AWG Cu/Al,CH,Type CH Loadcenters
Product Type	CH15096-4604-11TYPE CH Breaker 50A/1 Pole 120/240V 10K

Manufacturer Information

Brand	EATON CUTLER-HAMMER
GTIN	00782113101682
Manufacturers Part Number	CH150
UPC	782113101682

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Category Description	Loadcenter Plug In Breakers and Accessories
Type	Thermal magnetic circuit breakers

Availability

Status	Inactive

Packaging

Carton	1
Weight Per each	0.28

Uses, Certifications, and Standards

standard	UL 489