

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UPC

CH250GF 2P 50A Ground Fault Breaker *Faton Corp*

CIET STATE	Eaton Corp	
Catalog I	Number	CH250GF
Manufac	cturer	Eaton Corp
Descript	ion	Eaton CH Gfci Circuit Breaker, Ground Fault Circuit Breaker, 50 A, 10 Kaic, Two-Pole, 120/240 V, CH, Common, Plug-On, #14-6 Awg Cu/Al, Type CH Loadcenters, Ground Fault Circuit Interrupter, GFI
Weight p	oer unit	0.9800 (lbs/each)
Product	Category	In Circuit Breakers
Features		
amperag	ge rating	50 A
connecti	on	Plug-on
interrup	t rating	10 kAIC
Poles		Two-pole
Trip Type	e	Common
Voltage	Rating	120/240 V
Dimensions	and Weight	
Height		2 in
Length		6 in
Width		2 in
Description	S	
Descript		2P 50A GROUND FAULT BREAKER
	ng description	ETN CH250GF
Features		Eaton's residential CH circuit breakers provide premium overload protection. The Type CH circuit breakers trip to the OFF position, eliminating nuisance callbacks. The CHF family also includes a trip flag to differentiate between a trip and the breaker being turned off. The thermal-magnetic trip curve avoids nuisance tripping on mild overloads while reacting almost instantaneously to severe short-circuit conditions. Multiple breakers have an internal common trip connection to operate all poles simultaneous
Long Des	scription	Eaton CH GFCI circuit breaker, Ground fault circuit breaker, 50 A, 10 kAIC, Two-pole, 120/240 V, CH, Common, Plug-on, #14-6 AWG Cu/AI, Type CH Loadcenters, Ground fault circuit interrupter, GFI
Product	Туре	CH250GF
Manufactui	rer Information	
Brand		EATON CUTLER-HAMMER
GTIN		00782113912899
Manufac		

782113912899



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Cate	gories
Category Description	Fault Sensing Breakers (AFCI/GFCI)
Туре	GFCI circuit breakers
Packaging	
Carton	1
Weight Per each	0.98
Uses, Certifications, and Standards	
standard	UL 489