

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

12555 Harris Branch Pkwy Suite 105 78653-0000, TX Manor Phone: 512-339-8750

Fax: 512-339-6732



Special Features

CH2L40SP 1 PH/CH Loadcntr 40A MIo 2/4 Cir. Cu Bus Surface C Eaton Corp

	OUGLAGED
Catalog Number	CH2L40SP
Manufacturer	Eaton Corp
Description	Eaton CH Main Lug Loadcenters, Standard, Main Lug Only, 40A, 5, Copper, Nema 1, Metallic, Top/Bottom, CH, Surface, 2, Four-Pole, 2, Three-Wire, Single-Phase, 120/240 V, #14-6 Awg
Weight per unit	3.3 (lbs/each)
Product Category	Single Phase Main Lug Load Cen
eatures	
amperage rating	40
interrupt rating	25
media	Yes
number of spaces	2
Phase	1
Voltage Rating	120/240 V
Wattage	Four-pole
Dimensions and Weight	
Depth	22.2
Height	4.1
Size	5
Width	15.1
Descriptions	
Description	1 PH/CH LOADCNTR 40A MLO 2/4 CIR. CU BUS SURFACE C
extra long description	ETN CH2L40SP 1 Ph/CH LC 40A MLO 2/4
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box or even a fuse box, the main function is to take electricity supplied by the utility and distribute it throughout the home to feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.
Long Description	Eaton CH main lug loadcenters, Standard, Main lug only, 40A, 5, Copper, NEMA 1, Metallic, Top/bottom, CH, Surface, 2, Four-pole, 2, Three-wire, Single-ph V, #14-6 AWG
Product Type	1 PH/CH LC 40A MIo 2/4 CKT Cu Bus Surf
J	

Standard



ELLIOTT ELECTRIC SUPPLY 12555 Harris Branch Pkwy Suite 105 78653-0000, TX Manor Phone: 512-339-8750 509: 512-339-8732

We Deliver...Lower Cost, Quality Products, & Personal Service

Fax: 512-339-6732

	Inform	

Brand	EATON CUTLER-HAMMER
GTIN	00782114190418
Manufacturers Part Number	CH2L40SP
UPC	782114190418

Taxonomies, Classifications, and Categories

Category Description	LOADCENTERS & COVERS
Туре	Main lug loadcenter

Packaging

onaging	
Carton	1
Weight Per each	3.3

Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
Mounting	Surface Mount
standard	UL 67,UL 50