



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



CHFGF115PN 1P 15A 120V TF Gfci PN Breaker *Eaton Corp*

Catalog Number	CHFGF115PN
Manufacturer	Eaton Corp
Description	Eaton CH Gfci Circuit Breaker, Ground Fault Circuit Breaker, Trip Flag, Gfci, 156 A, 10 Kaic, Single-Pole, 120/240 V, CHFGF, Plug-On Neutral, Ground Fault Circuit Interrupter, GFI
Weight per unit	0.8000 (lbs/each)
Product Category	In Circuit Breakers

Features

amperage rating	156A
connection	Plug-on neutral
dimensions	6.0000 IN X 3.5000 IN X 1.0000 IN
interrupt rating	10
Poles	1
Voltage Rating	120/240 V

Descriptions

Description	1P 15A 120V TF GFCI PN BREAKER
extra long description	ETN CHFGF115PN Eaton CH GFCI circuit
Features	Eaton's residential CH circuit breakers provide premium overload protection. The Type CH circuit breakers trip to the OFF position, eliminating nuisance callbacks. The CHF family also includes a trip flag to differentiate between a trip and the breaker being turned off. The thermal-magnetic trip curve avoids nuisance tripping on mild overloads while reacting almost instantaneously to severe short-circuit conditions. Multiple breakers have an internal common trip connection to operate all poles simultaneous
Long Description	Eaton CH GFCI circuit breaker, Ground fault circuit breaker, Trip flag, GFCI, 156 A, 10 kAIC, Single-pole, 120/240 V, CHFGF, Plug-on neutral, Ground fault circuit interrupter, GFI
Product Type	Eaton CH Gfci Circuit Breaker
Special Features	Trip flag, GFCI

Manufacturer Information

Brand	Eaton
GTIN	00786685546254
Manufacturers Part Number	CHFGF115PN
UPC	786685546254

Taxonomies, Classifications, and Categories

Category Description	Fault Sensing Breakers (AFCI/GFCI)
Type	GFCI circuit breakers



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Availability

Status	Inactive
--------	----------

Packaging

Carton	1
--------	---

Weight Per each	0.8
-----------------	-----

Uses, Certifications, and Standards

Application	Datacenters - IT Space: CI and Hyper ConvergedOtherGeneration - Renewable Energy - Alternative EnergyGeneration - Conventional Energy - Conventional EnergyMarine Vessels and Equipment - Marine Vessels and Equipment - Other
standard	UL 489