



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

CHMS Blank Dead Front Directory Marking Strip

Eaton Corp

Catalog Number	CHMS
Manufacturer	Eaton Corp
Description	Eaton CH 3/4-Inch Loadcenter and Breaker Accessories - Circuit Marking Strip, Circuit Marking Strip, CH, 0.75 In, Used With Type CH Style 3/4 In Loadcenter and Breakers
Weight per unit	0.1000 (lbs/each)
Product Category	Load Center Accessories

Features

amperage rating	225 A
dimensions	4.0000 IN X 7.0000 IN X 0.0100 IN
interrupt rating	10 kAIC
media	Yes
Phase	Three-phase

Dimensions and Weight

Depth	4.0000
Height	0.0100
Width	7.0000

Descriptions

Description	BLANK DEAD FRONT DIRECTORY MARKING STRIP
extra long description	ETN CHMS Blank Dead Front Directory
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for power distribution and circuit protection in residential and light commercial applications. Also called a breaker box, electrical box or even a fuse box, the main function is to take electricity supplied by the utility and distribute it throughout the home to feed lights and receptacles. Covers are typically packaged separately and available as surface or flush mount.
Long Description	Eaton CH 3/4-inch Loadcenter and Breaker Accessories - Circuit Marking Strip,Circuit marking strip,CH,0.75 in,Used with Type CH Style 3/4 in Loadcenter and Breakers
Product Type	Blank Dead Front Directory Marking Strip
Special Features	Used with Type CH Style 3/4 in Loadcenter and Breakers

Manufacturer Information

Brand	EATON CUTLER-HAMMER
GTIN	00782113099729
Manufacturers Part Number	CHMS
UPC	782113099729



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685

Taxonomies, Classifications, and Categories

Type	Accessory
------	-----------

Packaging

Carton	1
--------	---

Package	10
---------	----

Weight Per each	0.1
-----------------	-----

Uses, Certifications, and Standards

Application	Other
-------------	-------

standard	UL 489
----------	--------