

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Eaton Corp Catalog Number	CHN230GF
Manufacturer	Eaton Corn
Description	Eaton CH Gfci Circuit Breaker, Plug-In Circuit Breaker, 30 A, 10 Kaic, Two-Pole, 120/240 V, CH, Common, GFI, 5 Ma
Weight per unit	
Product Category	In Circuit Breakers
eatures	
amperage rating	30 A
dimensions	3.5000 IN X 3.5000 IN X 2.2500 IN
interrupt rating	
Poles	
Trip Type	
Voltage Rating	
escriptions	
Description	CH 5MA GFCI 2P 30A 120/240V 10KAIC
extra long description	ETN CHN230GF CH 5mA GFCI, 2P, 30A,
Features	Eaton's residential CH circuit breakers provide premium overload protection. The Type CH circuit breakers trip to the OFF position eliminating nuisance callbacks. The CHF family also includes a tri flag to differentiate between a trip and the breaker being turned off. The thermal-magnetic trip curve avoids nuisance tripping on mild overloads while reacting almost instantaneously to severe short-circuit conditions. Multiple breakers have an internal common trip connection to operate all poles simultaneous
Long Description	Eaton CH GFCI circuit breaker,Plug-in circuit breaker,30 A,10 kAIC,Two-pole,120/240 V,CH,Common,GFI,5 mA
Product Type	CH 5MA Gfci, 2P, 30A, 120/240V, 10kaic
Nanufacturer Information	
Brand	Eaton Corp
GTIN	00786689217242
Manufacturers Part Number	CHN230GF
UPC	786689217242
axonomies, Classifications, and C	Categories (Categories)
Туре	GFCI circuit breakers
ackaging	
Carton	1
Weight Per each	0.95



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

Application

standard

Datacenters - IT Space: CI and Hyper ConvergedGeneration -Conventional Energy - Conventional EnergyOtherGeneration -Renewable Energy - Alternative EnergyMarine Vessels and Equipment - Marine Vessels and Equipment - Other UL 489