

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



CHN250GF CH 5MA Gfci 2P 50A 120/240V 10kaic Eaton Corp

Catalog Number	CHN250GF
Manufacturer	Eaton Corp
Description	Eaton CH Gfci Circuit Breaker, Plug-In Circuit Breaker, 50 A, 10 Kaic, Two-Pole, 120/240 V, CH, Common, GFI, 5 Ma
Weight per unit	0.8100 (lbs/each)
Product Category	In Circuit Breakers

Features

amperage rating	50 A
dimensions	6.0000 IN X 3.5000 IN X 2.2500 IN
interrupt rating	10
Poles	2
Trip Type	Common 120/240 V
VOITAGE NATIO	120/240 V

Descriptions

Description	CH 5MA GFCI 2P 50A 120/240V 10KAIC
extra long description	ETN CHN250GF CH 5mA GFCI, 2P, 50A,
Features	Eaton's residential CH circuit breakers provide premium overload protection. The Type CH circuit breakers trip to the OFF position, eliminating nuisance callbacks. The CHF family also includes a trip flag to differentiate between a trip and the breaker being turned off. The thermal-magnetic trip curve avoids nuisance tripping on mild overloads while reacting almost instantaneously to severe short-circuit conditions. Multiple breakers have an internal common trip connection to operate all poles simultaneous
Long Description	Eaton CH GFCI circuit breaker,Plug-in circuit breaker,50 A,10 kAIC,Two-pole,120/240 V,CH,Common,GFI,5 mA
Product Type	CH 5MA Gfci, 2P, 50A, 120/240V, 10kaic

Manufacturer Information

Eaton Corp
00786689217280
CHN250GF
786689217280

Taxonomies, Classifications, and Categories

Category Description	Fault Sensing Breakers (AFCI/GFCI)
Туре	GFCI circuit breakers

Packaging

Carton	1
Weight Per each	0.81

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Uses, Certifications, and Standards

	aridards
Application	Marine Vessels and Equipment - Marine Vessels and Equipment -
	OtherOtherDatacenters - IT Space: CI and Hyper
	ConvergedGeneration - Renewable Energy - Alternative
	EnergyGeneration - Conventional Energy - Conventional Energy
standard	UL 489