

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Long Description

Product Type

CHP32N225X6 CH Pon Loadcntr 225A Convertible 32 Spaces *Eaton Corp*

Eaton Corp	
Catalog Number	CHP32N225X6
Manufacturer	Eaton Corp
Description	Eaton CH Plug-On Neutral Loadcenter, 225A, Convertible, 32
	Spaces
Weight per unit	18.9 (lbs/each)
Product Category	Single Phase Convertible Load
Features	
amperage rating	225 A
Cover Type	V/
dimensions	34.1200 IN X 14.3100 IN X 3.8800 IN
interrupt rating	25 kAIC
media	Yes
number of spaces	32
Phase	Single-phase
Voltage Rating	
Wattage	
Dimensions and Weight	
Depth	34.1200
Height	
Size	Х6
Width	14.3100
Descriptions	
Description	CH PON LOADCNTR 225A CONVERTIBLE 32 SPACES
extra long description	ETN CHP32N225X6 CH PON LC, 225A, CO
Features	Eaton's CH 3/4-inch loadcenters enclose CH circuit breakers for
. outur os	power distribution and circuit protection in residential and light
	commercial applications. Also called a breaker box, electrical box
	or even a fuse box, the main function is to take electricity
	supplied by the utility and distribute it throughout the home to
	feed lights and receptacles. Covers are typically packaged
	separately and available as surface or flush mount.

spaces

CH Pon LC, 225A, Conv, 32SP

Eaton CH plug-on neutral loadcenter, 225A, convertible, 32



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

n	/lanufac	HILPAR	INTARMA	tion

Brand	Eaton	
GTIN	00786689055196	
Manufacturers Part Number	CHP32N225X6	
UPC	786689055196	

Taxonomies, Classifications, and Categories

Category Description	LOADCENTERS & COVERS
Туре	Convertible loadcenter

Packaging

onaging	
Carton	1
Weight Per each	18.9

Uses, Certifications, and Standards

Application	Residential Bldgs & Facilities - Residential Bldgs & Facilities -
	Other
standard	UL 67,UL 50