



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.
75964-0000, TX Nacogdoches
Phone: 936-569-7941
Fax: 936-560-4685



CHSPT2SURGE Singleph- UL1449 3RD Edition- Type 2 SPD *Eaton Corp*

Catalog Number	CHSPT2SURGE
Manufacturer	Eaton Corp
Description	Single Receptacle, 36 Ka, 120/240 V Ac, SPDT Connection, 60 HZ, 7.5 In Length, 5 In Width, 2.53 In Height, 3 LB
Weight per unit	3.0 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro

Features

dimensions	7.5000 IN X 5.0000 IN X 2.0000 IN
Phase	Single-phase
Short Circuit Rating	22000 KA

Descriptions

Description	SINGLEPH- UL1449 3RD EDITION- TYPE 2 SPD
extra long description	ETN CHSPT2SURGE 1PH: UL1449 3RD EDI
Features	Eaton offers a comprehensive family of surge products for use at service entrances. These products can help protect sensitive electronics against the damaging effects of surges. Due to the evolution of electronics and microprocessors in the home, there is a continuous challenge to provide quality (clean) power for electronic loads such as appliances, computers/home office and entertainment systems. Surges caused by lightning, utility grid switching and other sources travel on current carrying conductors t

Manufacturer Information

GTIN	00786685971285
UPC	786685971285

Taxonomies, Classifications, and Categories

Category Description	SURGE SUPPRESSION PRODUCTS
Type	Surge protection device

Packaging

Carton	1
Weight Per each	3

Uses, Certifications, and Standards

Application	Residential Bldgs & Facilities - Residential Bldgs & Facilities - Other
Frequency Rating	60 Hz
Operating Temperature	-40 to 50 °C
standard	UL Recognized,UL 1449,cUL Certified