

# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

7520 Eastgate Blvd Suite 100 37122-0000, TN Mt. Juliet Phone: 615-257-4146

Fax: 615-257-4147



## **CPR28 3" Rigid Coupling Threadless** *Crouse-Hinds*

-1473	
Catalog Number	CPR28
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series CPR Compression Coupling, Rigid/Imc, Malleable Iron, Compression Type, 3"
Weight per unit	4.5 (lbs/each)
Product Category	Rigid Conduit Fittings - Steel
Features	
dimensions	5.2000 IN X 5.6000 IN X 5.6000 IN
Material	Malleable Iron
<b>Descriptions</b>	
Description	3" RIGID COLIDI ING THREADI ESS

#### Des

Description	3" RIGID COUPLING THREADLESS
extra long description	MIDWEST CPR28 3 RGD CMP CPL
Features	Crouse-Hinds series rigid/IMC connectors, couplings and combination couplings are used to join used to join rigid/IMC conduit to a box or enclosure, or to couple two ends of conduit together. Our rigid/IMC connectors and couplings are available in set screw type and compression type, in both insulated and non-insulated versions. They are available in a variety of materials to suit customer preferences, including malleable iron, steel, zinc die cast, aluminum, stainless steel and hot dip galvanized mallea
Long Description	Eaton Crouse-Hinds series CPR compression coupling, Rigid/IMC, Malleable iron, Compression type, 3"
Product Type	3 RGD CMP CPL
Special Features	Concrete Tight

#### **Manufacturer Information**

Brand	Eaton
GTIN	00784564122285
Manufacturers Part Number	CPR28
UPC	784564122285

### Taxonomies, Classifications, and Categories

Category Description	Watertight Hub, 3-PIECE COUPLINGS, THREADLESS COUPLINGS
	AND THREADLESS CONNECTOR
Туре	Compression coupling

## **Packaging**

Carton	1
Weight Per each	4.5

7520 Eastgate Blvd Suite 100 37122-0000, TN Mt. Juliet Phone: 615-257-4146 Fax: 615-257-4147

#### **Uses, Certifications, and Standards**

Application	Commercial / Institutional Buildings / Structures - Commercial /
	Institutional Buildings / Structures - Other
standard	UL 514B, CUL