


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Special Features

CS8369 Lock"G RCPT, 50A 3PH 250V, 3P4W Hubbell Wiring Devices

Catalog Number	CS8369	
Manufacturer	Hubbell Wiring Devices	
Description	Locking Devices, Twist-Lock®, Industrial, Receptacle, 50A 3-Phase Delta 250V Ac, 3-Pole 4-Wire Grounding, Non-Nema, Screw Terminal, Black	
Weight per unit	0.7500 (lbs/each)	
Product Category	Gen Purpose Recept & Surge Pro	
Features		
amperage rating	50	
connection	Screw Terminal	
Current Rating	50	
Dielectric Strength	Withstands 2,000V minimum	
Number of Wires		
pallet quantity	1680	
Phase	3	
Poles	3-Pole	
Voltage Rating	3-Phase Delta 250 VAC	
Wattage	12,500	
Wire Size	#10 to #6	
Dimensions and Weight		
Size	2.69 in x 2.12 in x 2.36 in	
Descriptions		
Description	LOCK"G RCPT, 50A 3PH 250V, 3P4W	
extra long description	HWDK CS8369 LOCKING RCPT, 50A 3PH 2	
Features	Hubbell's 50 Amp Twist-Lock® Devices feature a heavy-duty	
	design and super-tough nylon housing built for heavy-duty	
	applications and impact resistance, even in the harshest	
	environments. Their rigid construction restricts contact	
	distortion, minimizing the possibility of mating dissimilar devices	
	The cord grip's offset gripping jaws securely hold the conductors and the cord jacket for excellent strain relief.	
Long Description	Locking Devices, Twist-Lock®, Industrial, Receptacle, 50A 3-Phase Delta 250V AC, 3-Pole 4-Wire Grounding, Non-NEMA, Screw Terminal, Black	
Product Type	Locking RCPT, 50A 3PH 250V, 3P4W	
- · · -	and the second of the second o	

Standard Product



ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Manufacturer Inform

Brand	WIRING DEVICE-KELLEMS
GTIN	00783585829074
Manufacturers Part Number	CS8369
UPC	783585829074

Taxonomies, Classifications, and Categories

Category Description	NEMA RATED TURNLOK PLUGS, CONNECTORS, & RECEPTICLES
Туре	RECEPTACLE

Packaging

Maging		
Carton	1	
Package	10	
Weight Per each		

Uses, Certifications, and Standards

Application	Heavy Duty Industrial
environmental conditions	Indoor Dry unless protected by additional means
Mounting	Screw Mount
nema rating	Non-NEMA
standard	Certified to CSA C22.2 No.42;Listed to UL 498