

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



Weight Per each

## CVS2125XMM CVS 2P 125AS 42KA 240 Vac Load Terms W/Hardware Eaton Corp

Catalog Number	CVS2125XMM
Manufacturer	Eaton Corp
Description	Eaton Type CV Molded Case Circuit Breaker, Molded Case Circuit Breaker, 125 A, 42 Kaic, Two-Pole, #6 - 4/0 Al/Cu, CV, #4/0 Kcmil Maximum Load, Includes Mounting Kit
Weight per unit	3.0 (lbs/each)
Product Category	2 Pole
Features	
Current Rating	125 A
dimensions	7.5000 IN X 3.5000 IN X 5.0000 IN
Poles	Two-pole
Descriptions	
Description extra long description	CVS 2P 125AS 42KA 240 VAC LOAD TERMS W/HARDWARE ETN CVS2125XMM CVS 2 POLE 125 AMPS
Features	Eaton's main circuit breakers are used in a variety of applications including the main or emergency disconnect on the outside of a house, a tenant main breaker in group metering stacks and feed-through lug blocks specifically designed for sub-feeding from an existing panel. Main breakers are available with a variety of accessories including shunt trip, bell alarms and auxiliary switches.
Long Description	Eaton Type CV Molded Case Circuit Breaker, Molded case circuit breaker, 125 A, 42 kAIC, Two-pole, #6 - 4/0 AI/Cu, CV, #4/0 kcmil maximum load, Includes mounting kit
Product Type	CVS 2 Pole 125 Amps 42KA 240 Vac
Manufacturer Information	
Brand	Eaton
GTIN	00786685705897
Manufacturers Part Number	CVS2125XMM
UPC	786685705897
Taxonomies, Classifications, and	Categories
Category Description	MAOLDED CASE DDEAVEDS
Туре	Tenant main breaker
Packaging	
Carton	1

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## Uses, Certifications, and Standards

	unduras
Application	Generation - Renewable Energy - Alternative
	EnergyOtherGeneration - Conventional Energy - Conventional
	EnergyDatacenters - IT Space: CI and Hyper ConvergedMarine
	Vessels and Equipment - Marine Vessels and Equipment - Other
standard	CSA Std. C22.2 No. 5.UL 489