

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## CVX050240H CVX050-240H Efa Asm Eaton Power Quality

Catalog Number	CVX050240H
Manufacturer	Eaton Power Quality
Description	Surge Protection Device, CVX050 Series, 50 Kaic, 240V, 480V, 600V, 300 L-L, 150 L-N, 150 L-G, 640 N-G Operating Voltage, Three-Phase
Weight per unit	2.0 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro
Features	
dimensions	3.5500 IN X 4.7500 IN X 5.6700 IN
Phase	Three-phase
Voltage Rating	240 V, 480 V, 600 V
Dimensions and Weight	
Depth	3.5500
Height	5.6700
Width	4.7500
Descriptions	
Description	CVX050-240H EFA ASM
extra long description	ETN CVX050-240H Eaton CVX surge pro
Features	Eaton's CVX050 and CVX100 Surge Protective Devices (SPDs) ensure that a customer's investment in equipment and processes are protected from the damaging effects of voltage transients. Designed for installation on service entrance, branch panels, or individual equipment disconnects, the CVX series provides enhanced surge protection for mission-critical applications. Available in configurations and current capacities of 50 or 100 kA per phase.
Long Description	Surge Protection Device, CVX050 series, 50 kAIC, 240V, 480V, 600V, 300 L-L, 150 L-N, 150 L-G, 640 N-G operating voltage, Three-phase
Product Type	Eaton CVX Surge Protection Device
Manufacturer Information Brand	Eaton
GTIN	00786685514642
Manufacturers Part Number	CVX050-240H

## **Taxonomies, Classifications, and Categories**

**UPC** 

Category Description	SURGE SUPRESSION PRODUCTS
Туре	Surge protection device

786685514642



## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Packaging	
Carton	1
Weight Per each	2
Uses, Certifications, and Standard	ls
Application	Elec Assemblies, Panels & EOEM - Electrical Assemblies and
	EOEMs - Other
standard	UL 1449