

### DIELESS HYDRAULIC CRIMPING TOOLS



#### Dieless 500

- Crimps copper or aluminum up to 500 MCM
- Dieless crimping head – no dies to lose or replace
- Patented pressure system automatically changes crimping force. for each connector size and type
- Seven-indent profile requires fewer crimps per connector
- Automatic two-speed pump for rapid advance
- Crimping head rotates 180°.
- 8.5 ton max crimping force



#### Dieless 1000

- Crimps copper or aluminum up to 1000 MCM
- Dieless crimping head – no dies to lose or replace
- Patented pressure system automatically changes crimping force for each connector size and type
- Automatic two-speed pump for rapid advance.
- 15 ton max crimping force.

| CATALOG NO. | UPC NO. | WIRE RANGE AL-CU |                    | WEIGHT LBS. | LENGTH |
|-------------|---------|------------------|--------------------|-------------|--------|
|             |         | MAX.             | MIN.               |             |        |
| D-500       | 67002   | 500 MCM          | 6 AWG-AL, 4 AWG-CU | 14.75       | 22.5   |
| D-1000      | 67003   | 1000 MCM         | 6AWG-AL, 4 AWG-CU  | 32          | 26.5   |

### BATTERY-OPERATED DIE TYPE CRIMPING TOOL



#### Power 750

- 14.6 tons, 1.65" jaw opening for U-type dies
- Powerful 14.4 Volt battery crimper
- High power Ni-Cad battery
- Head rotates through 180°
- Reinforced molded nylon body
- Pressure release button
- Switch protected against accidental operation
- Battery condition display
- Balanced tool and sculptured body for greater control
- Ergonomically designed center grip handle
- 10,000 PSI rated operating pressure
- Includes steel carrying case, shoulder strap, spare battery and battery charger.

| CATALOG NO. | UPC NO. | WIRE RANGE AL-CU |       | WEIGHT LBS. | LENGTH |
|-------------|---------|------------------|-------|-------------|--------|
|             |         | MAX.             | MIN.  |             |        |
| P-750       | 66999   | 750 MCM          | 8 AWG | 15.4        | 16.5   |

**DIELESS HYDRAULIC CRIMPING TOOLS**

**Dieless 500**

- Crimps copper or aluminum up to 500 MCM
- Dieless crimping head – no dies to lose or replace
- Patented pressure system automatically changes crimping force. for each connector size and type
- Seven-indent profile requires fewer crimps per connector
- Automatic two-speed pump for rapid advance
- Crimping head rotates 180°.
- 8.5 ton max crimping force


**Dieless 1000**

- Crimps copper or aluminum up to 1000 MCM
- Dieless crimping head – no dies to lose or replace
- Patented pressure system automatically changes crimping force for each connector size and type
- Automatic two-speed pump for rapid advance.
- 15 ton max crimping force.

| CATALOG NO. | UPC NO. | WIRE RANGE AL-CU |                    | WEIGHT LBS. | LENGTH |
|-------------|---------|------------------|--------------------|-------------|--------|
|             |         | MAX.             | MIN.               |             |        |
| D-500       | 67002   | 500 MCM          | 6 AWG-AL, 4 AWG-CU | 14.75       | 22.5   |
| D-1000      | 67003   | 1000 MCM         | 6AWG-AL, 4 AWG-CU  | 32          | 26.5   |

**BATTERY-OPERATED DIE TYPE CRIMPING TOOL**

**Power 750**

- 14.6 tons, 1.65" jaw opening for U-type dies
- Powerful 14.4 Volt battery crimper
- High power Ni-Cad battery
- Head rotates through 180°
- Reinforced molded nylon body
- Pressure release button
- Switch protected against accidental operation
- Battery condition display
- Balanced tool and sculptured body for greater control
- Ergonomically designed center grip handle
- 10,000 PSI rated operating pressure
- Includes steel carrying case, shoulder strap, spare battery and battery charger.

| CATALOG NO. | UPC NO. | WIRE RANGE AL-CU |       | WEIGHT LBS. | LENGTH |
|-------------|---------|------------------|-------|-------------|--------|
|             |         | MAX.             | MIN.  |             |        |
| P-750       | 66999   | 750 MCM          | 8 AWG | 15.4        | 16.5   |