

## ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



## D93250ACZ1 SSR-Hockpuck 50A 24-280VAC Out, 90-280VAC In, Zero C Eaton Corp

Catalog Number	D93250ACZ1
Manufacturer	Eaton Corp
Description	D93 Series Solid-State Relay, 90-280V Input Voltage, 24-280V Output Voltage, Zero Cross Switching Type, 50A Rated Operational Current, Green Led, SPST-No Contact Configuration, IP20 Enclosure
Woight por unit	0.3000 (lbs/each)
Weight per unit Product Category	Monitoring Relays & Accy.
eatures	
dimensions	0.6600 IN X 2.2800 IN X 1.7400 IN
escriptions	
Description	SSR-HOCKPUCK 50A 24-280VAC OUT,90-280VAC IN,ZERO C
extra long description	ETN D93250ACZ1 SSR-HOCKPUCK 50A 24-
Features	Eaton's solid-state relays (SSR) are reliable, offer a long service life, significantly reduce electromagnetic interference, respond quickly and are resistant to vibration. Applications for solid-state relays typically include equipment that requires high cycling rates, low acoustical or electrical noise, or vibration resistance; such as material handling equipment, medical equipment, heating/cooling equipment, lighting control and pumps/compressors.
Long Description	D93 Series Solid-State Relay, 90-280V input voltage, 24-280V output voltage, Zero cross switching type, 50A rated operational current, Green LED, SPST-NO contact configuration, IP20 enclosure
Product Type	SSR-Hockpuck 50A 24-280VAC Out, 90-280vac
Manufacturer Information	
Brand	Eaton
GTIN	00786685219530
Manufacturers Part Number	D93250ACZ1
UPC	786685219530
axonomies, Classifications, and C	Categories
Category Description	(OO) A A A OUINE TO OUR DELAYO
Туре	Solid-state relay
ackaging	
Carton	1
Weight Per each	0.3

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

## **Uses, Certifications, and Standards**

Application	Commercial / Institutional Buildings / Structures - Power
	Distribution and Controls
standard	CSA Certified,UL 508,RoHS Compliant,CE Marked