


ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





DH365FGK 400A/3P HD Fusible Safety Switch 600V Nema 1 *Eaton Corp*

Catalan Namahan	DUDVEECK
Catalog Number Manufacturer	DH365FGK
Description	Eaton Corp Eaton Heavy Duty Single-Throw Fused Safety Switch, 400 A, Nema 1, Painted Steel, Class H, Fusible Without Neutral, Three-Pole, Three-Wire, 600 V, Max HP: 250, 350 HP (3PH @480/600 V), (2)#1/0-(2)300 Kcmil; or (1)#1/0-(1)750 Kcmil Al
Weight per unit	105.0 (lbs/each)
Product Category	Fusible Heavy Duty Safety Swit
Features	
amperage rating	400
dimensions	45.5000 IN X 24.3800 IN X 10.2500 IN
Material	Painted Steel
media	Yes
Poles	3
Voltage Rating	600 V
Dimensions and Weight	
Depth	45.5000
Height	10.2500
Width	24.3800
Descriptions	
Description	400A/3P HD FUSIBLE SAFETY SWITCH 600V NEMA 1
extra long description	ETN DH365FGK 400A/3P HD Fusible Sft
Features	Eaton's heavy-duty safety switches provide a highly visible mean of disconnect to help improve personnel safety and equipment protection. Additionally, they're Ideal for applications where reliable performance, safety, and service continuity are critical.
Long Description	Eaton Heavy duty single-throw fused safety switch, 400 A, NEMA 1, Painted steel, Class H, Fusible without neutral, Three-pole, Three-wire, 600 V, Max Hp: 250, 350 hp (3PH @480/600 V), (2)#1/0-(2)300 kcmil; or (1)#1/0-(1)750 kcmil Al
Product Type	400A/3P HD Fusible Sfty SW 600V N1
Manufacturer Information	
Brand	EATON CUTLER-HAMMER
GTIN	00782113207209
Manufacturers Part Number	DH365FGK
UPC	782113207209



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories		
Category Description	DISCONNECTS	
Туре	Fusible safety switch	
Packaging		
Carton	1	
Weight Per each	105	
Uses, Certifications, and Stand	ards	
Application	Commercial / Institutional Buildings / Structures - Power	
	Distribution and Controls	
nema rating	1	

UL Listed, NEC 230.62 (C) Compliant Barrier