ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
3101 Industrial Terrace
Austin, TX 78758-0000
Phone: 5123513290
Fax: 5129739027

DP30C3P2 3P 30A 208/240V DP CONTACTOR

INDUSTRIAL CONNECTIONS &

Catalog Number	DP30C3P2
Manufacturer	INDUSTRIAL CONNECTIONS &
Description	DP CONTR 3P 240 SCREW
Weight per unit	1,020.0 (lbs/each)
Product Category	Definite Purpose Contactors

Features

Auxiliary Contact	3NO
Coil Voltage	208/240 VAC
Construction Standard	IEC, EN 60947-4-1
Current Rating	30 AMPERE
Poles	3 in
Power Rating/Voltage	2 HP at 120 V, 5 HP at 240 V 1-Phase, 10 HP at 200/208/240/277 V, 15 HP at 480 V, 20 HP at 600 V 3-Phase
Resistive Ampere	40 AMPERE

Dimensions and Weight

Size	3.09 Inch W x 2.98 Inch D x 3.39 Inch H

ELLIOTT ELECTRIC SUPPLY
We Deliver...Lower Cost, Quality Products, & Personal Service
3101 Industrial Terrace
Austin, TX 78758-0000
Phone: 5123513290
Fax: 5129739027

Descriptions

Additional Information	Locked Rotor Rating 180 Ampere at 240/277 V, 150 Ampere at 480 V, 120 Ampere at 600 V; Application Motor, Power Supply, Food Service Equipment, Compressor, Business Machine, Resistive Heating, Air Conditioning, Refrigeration Equipment, Welding
Commodity Description	DEFINITE PURPOSE CONTACTORS
Description	3P 30A 208/240V DP CONTACTOR
Long Description	DP CONTR 3P 240 SCREW
	DEFINITE PURPOSE CONTACTOR, NON-REVERSING TYPE; 3.09 INCH W X 2.98 INCH D X 3.39 INCH H SIZE; UL 508, CE, SEMKO APPROVAL; OPEN ENCLOSURE; 30 AMPERE CURRENT RATING; 3 POLE(S); IEC, EN 60947-4-1 CONSTRUCTION STANDARD; 208/240 VAC COIL VOLTAGE
Product Type	Definite Purpose Contactor
Extra Long Description	NON-REVERSING TYPE; 3.09 INCH W X 2.98 INCH D X 3.39 INCH H SIZE; UL 508, CE, SEMKO APPROVAL; OPEN ENCLOSURE; 30 AMPERE CURRENT RATING; 3 POLE(S); IEC, EN 60947-4-1 CONSTRUCTION STANDARD; 208/240 VAC COIL VOLTAGE; 3NO AUXILIARY CONTACT; 2 HP AT 120 V, 5 HP AT 240 V 1-PHASE, 10 HP AT 200/208/240/277 V, 15 HP AT 480 V, 20 HP AT 600 V 3-PHASE POWER RATING/VOLTAGE; 40 AMPERE RESISTIVE AMPERE; LOCKED ROTOR RATING 180 AMPERE AT 240/277 V, 150 AMPERE AT 480 V, 120 AMPERE AT 600 V; APPLICATION MOTOR, POWER SUPPLY,

Manufacturer Information

Brand	ABB
GTIN	00662019755601
Manufacturers Part Number	DP30C3P-2
UPC	988478

Taxonomies, Classifications, and Categories

Category Description	DP CONTACTORS
Type	NON-REVERSING

Packaging

Carton	1
Weight Per Each	1,020.0 (lbs/each)

Uses, Certifications, and Standards

Approval	UL 508, CE, SEMKO
Enclosure	OPEN