

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685





Ca	atalog Number	DR10250L
M	anufacturer	Panduit Corporation
De	escription	The Vibration Resistant Female Disconnect Is Made Of Brass and Is Tin-Plated. It Is Non-Insulated In Metallic Housing. It Has A Tab Size Of 0.250 X 0.032" (6.3 X 0.8 MM) and Supports A Wire Range Of 12-10 Awg (4.0-6.0 MM²). It Is 0.61" (15.5 MM) Long and 0.3" (7.6 MM) Wide. The Disconnect Has A Standard Barrel Configuration and A Sleeved Barrel. It Comes In Bottles Of 50.
W	eight per unit	1.0 (lbs/each)
Pr	oduct Category	Small Terminals & Connectors
Descri	ptions	
	escription	DISCONNECT
ex	tra long description	PAN DR10-250-L Pan-Term® DR10-250-L
Lo 	ong Description	The vibration resistant female disconnect is made of brass and is tin-plated. It is non-insulated in metallic housing. It has a tab size of 0.250 x 0.032" (6.3 x 0.8 mm) and supports a wire range of 12-10 AWG (4.0-6.0 mm²). It is 0.61" (15.5 mm) long and 0.3" (7.6 mm) wide. The disconnect has a standard barrel configuration and a sleeved barrel. It comes in bottles of 50.
Pr	oduct Type	Pan-Term® DR10-250-L Loose Piece Disconnect
Manu	facturer Information	
Br	and	PANDUIT
	ΓΙΝ	00074983827367
	anufacturers Part Number	DR10-250-L
UI	PC	074983827367
	omies, Classifications, and Category Description	
Packa	ging	
	arton	50
W	eight Per each	1