



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685



## DSD925 2CKT 3POS Sel-SW *Crouse-Hinds*

Catalog Number	DSD925
Manufacturer	Crouse-Hinds
Description	Control Station Cover, Electrogalvanized Aluminum Acrylic Painted Feraloy Iron Alloy Material, 4NO-2NC Contact Configuration, Maintained Switch Action, 2 Circuits, 3 Positions, 3.65 LB
Weight per unit	3.7 (lbs/each)
Product Category	Control Station Cover Assembl

### Features

action	Maintained
amperage rating	10
dimensions	5.0000 IN X 4.5000 IN X 3.5000 IN
Voltage Rating	600 VAC

### Descriptions

Description	2CKT 3POS SEL-SW
extra long description	CRS-H DSD925 DSD COVER DEVICE SUB A
Features	New DSDX series available with NEMA 4X protection for Class I, Division 2 hazardous areas.Crouse-Hinds series DSD and DSDX explosionproof cover and device sub-assemblies are for use with our EDS/EDSC back boxes and EDSCM modular multi-gang device bodies. DSD/DSDX covers are available with a wide variety of devices and configurations, including manual motor starters, front operated pushbuttons, general use snap switches, side operated pushbuttons, selector switches and pilot lights. Certified for use in CI

### Manufacturer Information

Brand	Eaton
GTIN	00782274776408
UPC	782274776408

### Taxonomies, Classifications, and Categories

Category Description	HAZARDOUS LOCATION MOTOR CONTROL
Type	Selector switch cover and device sub-assembly

### Packaging

Carton	1
Weight Per each	3.65



# ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr.  
75964-0000, TX Nacogdoches  
Phone: 936-569-7941  
Fax: 936-560-4685

## Uses, Certifications, and Standards

Application	Ind Facilities & Factories - Facility: Power Distribution and Control
Enclosure	Class I Div 1 2 Group B C D, Class II Div 1 Group E F G, Class II Div 2 Group F G, Class III, NEMA 3/7B/7C/7D/9E/9F/9G
standard	UL 1203, CSA C22.2