



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3706 Frankston Hwy
75701-0000, TX Tyler
Phone: 903-509-9882
Fax: 903-509-9832



DT8EHQ0 27" BLK Weather Res CBL Tie *Panduit Corporation*

Catalog Number	DT8EHQ0
Manufacturer	Panduit Corporation
Description	Panduit DT8EH-Q0 Dura-Ty™ Cable Ties Are Weather, Chemical, and Uv-Resistant For Harsh Outdoor Power and Communications Applications. The Durable Locking Mechanism, Complete With Double Stainless Steel Locking Barbs, Provides A Consistent, Reliable Connection and High-Impact Resistance and Strength. Extra-Heavy Cross Section, 27.0" (686MM) Length, Are Made Of Weather Resistant Acetal. They Are Black In Color and Come In Packages Of 25.
Weight per unit	0.0517 (lbs/each)
Product Category	Cable Ties & Wraps

Features

media	Yes
Tensile Strength	250

Dimensions and Weight

Length	27
Thickness	0.06

Descriptions

Description	27" BLK WEATHER RES CBL TIE
extra long description	PAN DT8EH-Q0 Dura-Ty™ DT8EH-Q0 Dura
Long Description	Panduit DT8EH-Q0 Dura-Ty™ Cable Ties are weather, chemical, and UV-resistant for harsh outdoor power and communications applications. The durable locking mechanism, complete with double stainless steel locking barbs, provides a consistent, reliable connection and high-impact resistance and strength. Extra-Heavy cross section, 27.0" (686mm) length, are made of Weather Resistant Acetal. They are black in color and come in packages of 25.
Product Type	Dura-Ty™ DT8EH-Q0 Dura-Ty Cable Tie, Black, Acetal, Uv, 27"L
Special Features	Indoor/Outdoor

Manufacturer Information

Brand	PANDUIT
GTIN	00074983789092
Manufacturers Part Number	DT8EH-Q0
UPC	074983789092



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3706 Frankston Hwy
75701-0000, TX Tyler
Phone: 903-509-9882
Fax: 903-509-9832

Taxonomies, Classifications, and Categories

Category Description Screws, Bolts, Staples, Jack Chains, Washers & TY-Raps
Type Cable Tie

Availability

minimum qty 25

Packaging

Carton 25

Package 250

Weight Per each 0.0517

Uses, Certifications, and Standards

standard UL 62275 (File #E56854), Type 2, 2S, CE TR-TSY-000789, RoHS
Compliant