



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3737 Grader Street Suite 120
75041-0000, TX Garland
Phone: 214-503-7227
Fax: 214-503-9766



DV18250MBCY 18-22AWG Red Insld ML Tab DSCNCT *Panduit Corporation*

| | |
|------------------|---|
| Catalog Number | DV18250MBCY |
| Manufacturer | Panduit Corporation |
| Description | The Vibration Resistant Male Disconnect Is Made Of Copper and Is Nickel-Plated. It Is Barrel Insulated In Red Vinyl Housing. It Has A Tab Size Of 0.250 X 0.032" (6.3 X 0.8 MM) and Supports A Wire Range Of 22-18 Awg (0.5-1.0 MM ²). It Is 0.98" (24.9 MM) Long and 0.25" (6.4 MM) Wide. The Disconnect Has A Funnel Entry Barrel Configuration and A Butted Seam Barrel. It Comes In Bottles Of 100. |
| Weight per unit | 0.3100 (lbs/each) |
| Product Category | Small Terminals & Connectors |

Features

| | |
|----------------|--------------|
| connection | Funnel Entry |
| insulation | Vinyl |
| Material | Copper |
| Voltage Rating | 600 |
| Wire Size | 18 |

Material, Color, and Finish

| | |
|--------|---------------|
| Color | Red |
| Finish | Nickel Plated |

Descriptions

| | |
|------------------------|---|
| Description | 18-22AWG RED INSLTD ML TAB DSCNCT |
| extra long description | PAN DV18-250MB-CY Pan-Term® DV18-25 |
| Long Description | The vibration resistant male disconnect is made of copper and is nickel-plated. It is barrel insulated in red vinyl housing. It has a tab size of 0.250 x 0.032" (6.3 x 0.8 mm) and supports a wire range of 22-18 AWG (0.5-1.0 mm ²). It is 0.98" (24.9 mm) long and 0.25" (6.4 mm) wide. The disconnect has a funnel entry barrel configuration and a butted seam barrel. It comes in bottles of 100. |
| Product Type | Pan-Term® DV18-250MB-Cy Loose Piece Disconnect |

Manufacturer Information

| | |
|---------------------------|----------------|
| Brand | Panduit® |
| GTIN | 00074983685622 |
| Manufacturers Part Number | DV18-250MB-CY |
| UPC | 074983685622 |



ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

3737 Grader Street Suite 120
75041-0000, TX Garland
Phone: 214-503-7227
Fax: 214-503-9766

Taxonomies, Classifications, and Categories

Category Description TERMINALS

Type Disconnect

Availability

minimum qty 100

Packaging

Carton 100

Weight Per each 0.31

Uses, Certifications, and Standards

Mounting 9/32

standard CSA Certified LR31212, C22.2 No.153;UL 310 Listed, UL Listed
20H3 E78522

Temperature Rating 221 Degrees Fahrenheit (105 Degrees Celsius)