

Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

10440 Airline Highway 70816-0000, LA Baton Rouge Phone: 225-292-7746 Fax: 225-292-7840



E10161605S Cam-Lock White Crouse-Hinds

| Catalog Number | E10161605S |
|------------------------|---|
| Manufacturer | Crouse-Hinds |
| Description | Eaton Crouse-Hinds Series Cam-Lok J Series E1016 Insulated Receptacle, Up to 400A Continuous, #6 Awg-250 Kcmil, White, Male, Thermoplastic Elastomer (Tpe), 1-1/8", Threaded Stud, 600 Vac/DC |
| Weight per unit | 1.0 (lbs/each) |
| Product Category | Gen Purpose Recept & Surge Pro |
| Features | |
| amperage rating | 400 |
| connection | 1-1/8 In Threaded Stud |
| dimensions | 3.6900 IN X 2.2500 IN X 2.2500 IN |
| insulation | TPE |
| Poles | |
| Voltage Rating | 600 VAC/VDC |
| Wire Size | 6 AWG TO 250 MCM |
| Dimensions and Weight | |
| Height | 2.25 |
| Width | 2.25 |
| Descriptions | |
| Description | CAM-LOCK WHITE |
| extra long description | CRS-H E1016-1605S E1016 M R THRD ST |
| Features | The Cam-Lok J series from Eaton's Crouse-Hinds Division provides the means to quickly connect and disconnect power systems safely. Cam-Lok is the industry standard for motors, generators, indoor and outdoor lighting distribution panels, and numerous other power applications. |
| Long Description | Eaton Crouse-Hinds series Cam-Lok J Series E1016 insulated receptacle, Up to 400A continuous, #6 AWG-250 kcmil, White, Male, Thermoplastic elastomer (TPE), 1-1/8", Threaded stud, 600 Vac/dc |
| Product Type | E1016 M R THRD Stud 1 1/8IN WH |
| Special Features | NEMA 3R Enclosure |



Elliott Electric Supply

We Deliver...Lower Cost, Quality Products, & Personal Service

10440 Airline Highway 70816-0000, LA Baton Rouge Phone: 225-292-7746 Fax: 225-292-7840

Manufacturer Information

| Brand | EATON CROUSE-HINDS SERIES |
|---------------------------------------|---|
| GTIN | 00662275128423 |
| Manufacturers Part Number | E1016-1605S |
| UPC | 662275128423 |
| Taxonomies, Classifications, and Cate | egories |
| Category Description | Dip & Sloove Devises |
| Туре | Insulated receptacle |
| Packaging | |
| Carton | 1 |
| Weight Per each | 1 |
| Uses, Certifications, and Standards | |
| Application | Ind Facilities & Factories - Facility: Power Distribution and Control |
| environmental conditions | -40 To 105 Deg C |
| Mounting | Threaded Panel |
| standard | UL 498, CSA C22.35 |