

ELLIOTT ELECTRIC SUPPLY 2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685



UPC

E10161633S 1-1/8" Red Female RCPT Crouse-Hinds

Catalog Number	E10161633S
Manufacturer	Crouse-Hinds
Description	Eaton Crouse-Hinds Series Cam-Lok J Series E1016 Insulated Receptacle, Up to 400A Continuous, #6 Awg-250 Kcmil, Red, Female, Thermoplastic Elastomer (Tpe), 1-1/8", Threaded Stud, 600 Vac/DC
Weight per unit	1.0 (lbs/each)
Product Category	Gen Purpose Recept & Surge Pro
eatures	
amperage rating	400
connection	1-1/8 In Threaded Stud
dimensions	3.6900 IN X 2.2500 IN X 2.2500 IN
insulation	TPE
Poles	1
Voltage Rating	600 VAC/VDC
Wire Size	6 AWG TO 250 MCM
imensions and Weight	
Height	2.25
Width	2.25
escriptions	
Description	1-1/8" RED FEMALE RCPT
extra long description	CRS-H E1016-1633S E1016 F R THRD ST
Features	The Cam-Lok J series from Eaton's Crouse-Hinds Division provid the means to quickly connect and disconnect power systems safely. Cam-Lok is the industry standard for motors, generators indoor and outdoor lighting distribution panels, and numerous other power applications.
Long Description	Eaton Crouse-Hinds series Cam-Lok J Series E1016 insulated receptacle, Up to 400A continuous, #6 AWG-250 kcmil, Red, Female, Thermoplastic elastomer (TPE), 1-1/8", Threaded stud, 600 Vac/dc
Product Type	E1016 F R THRD Stud 1 1/8IN RD
Special Features	NEMA 3R Enclosure
lanufacturer Information	
Brand	EATON CROUSE-HINDS SERIES
GTIN	00662275128591
Manufacturers Part Number	E1016-1633S

662275128591



standard

ELLIOTT ELECTRIC SUPPLY

We Deliver...Lower Cost, Quality Products, & Personal Service

2310 N. Stallings Dr. 75964-0000, TX Nacogdoches Phone: 936-569-7941 Fax: 936-560-4685

Taxonomies, Classifications, and Categories	
Category Description	Pin & Sleeve Devices
Туре	Insulated receptacle
Packaging	
Carton	1
Weight Per each	1
Uses, Certifications, and Standards	
Application	Ind Facilities & Factories - Facility: Power Distribution and Control
environmental conditions	-40 To 105 Deg C
Mounting	Threaded Panel

UL 498, CSA C22.66